

U.S. Patent Application  
Docket #27943-00415USP2  
Ericsson Ref. P14553US1

CERTIFICATE OF MAILING BY EXPRESS MAIL	
"EXPRESS MAIL"	
Mailing Label No.	EV 014 239 215 US . . . . .
Date of Deposit:	DECEMBER 21, 2001 . . . . .
I hereby certify that this paper or fee is being deposited with the U.S. Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to:	
Box PATENT APPLICATION Commissioner for Patents Washington, D.C. 20231	
Type or Print Name	DEBBIE HARGROVE . . . . .
Signature	<i>Debbie Hargrove</i> . . . . .

COMBINING NARROWBAND APPLICATIONS  
WITH BROADBAND TRANSPORT

## CROSS-REFERENCES TO RELATED APPLICATIONS

This U.S. Nonprovisional Application for Patent is a Continuation-in-Part of of U.S. Nonprovisional Application for Patent Serial No. 09/764,953, which was filed on  
5 January 17, 2001. U.S. Nonprovisional Application for Patent Serial No. 09/764,953 is also hereby incorporated by reference in its entirety herein.

This U.S. Nonprovisional Application for Patent is related by subject matter to U.S. Nonprovisional  
10 Applications for Patent Serial Nos. 09/\_\_\_\_,\_\_\_\_ (Attorney Docket No. 27493-00413USP2), filed December 6, 2001, 09/\_\_\_\_,\_\_\_\_ (Attorney Docket No. 27493-00414USP2), filed December 18, 2001, 09/\_\_\_\_,\_\_\_\_ (Attorney Docket No. 27493-00416USP2), filed December 12, 2001, and 09/\_\_\_\_,\_\_\_\_  
15 (Attorney Docket No. 27493-00422USP2), filed \_\_\_\_\_. These U.S. Nonprovisional Applications for Patent Serial Nos. 09/\_\_\_\_,\_\_\_\_, 09/\_\_\_\_,\_\_\_\_, 09/\_\_\_\_,\_\_\_\_, and 09/\_\_\_\_,\_\_\_\_

are hereby incorporated by reference in their entirety herein.

## BACKGROUND OF THE INVENTION

### Technical Field of the Invention

5           The present invention relates in general to the field of communications, and in particular, by way of example but not limitation, to using broadband transport for narrowband telephony and data communications.

### Description of Related Art

10           The increasing interest for high band services such as multimedia applications, video on demand, video telephone, and teleconferencing has motivated development of the Broadband Integrated Service Digital Network (B-

ISDN). B-ISDN is based on a technology known as Asynchronous Transfer Mode (ATM) and offers considerable extension of telecommunications capabilities.

ATM is a packet-oriented transfer mode which uses  
5 asynchronous time division multiplexing techniques. The packets are called cells and traditionally have a fixed size. A standard ATM cell comprises 53 octets, five of which form a header and 48 of which constitute a "payload" or information portion of the cell. The header of the ATM  
10 cell includes two quantities that are used to identify a connection in an ATM network over which the cell is to travel. These two quantities include the Virtual Path Identifier (VPI) and the Virtual Channel Identifier (VCI). In general, a virtual path is a principal path defined  
15 between two switching nodes of the network; a virtual channel is one specific connection on the respective principal path.

At its termination points, an ATM network is connected to terminal equipment, e.g., ATM network users. In between ATM network termination points, there are typically multiple switching nodes. The switching nodes  
5 have ports which are connected together by physical transmission paths or links. Thus, in traveling from an originating terminal equipment to a destination terminal equipment, ATM cells forming a message may travel through several switching nodes and the ports thereof.

10 Of the multiple ports of a given switching node, each may be connected via a link circuit and a link to another node. The link circuit performs packaging of the cells according to the particular protocol in use on the link. A cell that is incoming to a switching node may enter the  
15 switching node at a first port and exit from a second port via a link circuit onto a link connected to another node. Each link can carry cells for multiple connections, with each connection being, e.g., a transmission between a

calling subscriber or party and a called subscriber or party.

The switching nodes each typically have several functional parts, a primary of which is a switch core.

5 The switch core essentially functions like a cross-connect between ports of the switch. Paths internal to the switch core are selectively controlled so that particular ports of the switch are connected together to allow a message to travel from an ingress side/port of the switch to an

10 egress side/port of the switch. The message can therefore ultimately travel from the originating terminal equipment to the destination terminal equipment.

While ATM, because of the high speed and bandwidth that it offers, is envisioned as the transport mechanism

15 for more advanced services such as B-ISDN, it nevertheless must be recognized that the current narrowband networks (e.g., Public Switched Telephone Networks (PSTN), ISDN, etc.) will remain in use (at least in part) for quite some

time. It has taken decades for the present voice switched telephony networks (e.g., PSTN, ISDN, etc.) to reach their present advanced functionalities. While ATM networks are being built, the ATM networks will likely not easily  
5 acquire all the functionalities of advanced voice communication. Therefore, at least initially, ATM networks/nodes will in some instances be added to parts or will replace parts of circuit switched telephony networks. In such instances, ATM will be used for transport and  
10 switching. ATM can actually be used as a single transport and switching mechanism for multiple other networks, including multiple other different types of networks. For example, a single ATM network can be used to transport and switch communications from mobile networks (e.g., Public  
15 Land Mobile Networks (PLMNs)), Internet protocol (IP)-based networks (e.g., the Internet), etc., as well as landline networks such as PSTNs and ISDNs.

United States Patent Nos. 5,568,475 and 5,483,527 to Doshi et al., for example, incorporate ATM switches for routing telephony voice signals between Synchronous Transfer Mode (STM) nodes. The ATM switches use a signaling system No. 7 (SS#7) network to establish a virtual connection, rather than a circuit switched connection, as would be the case in a pure STM network. The signaling system No. 7 (SS#7) network of United States Patents 5,568,475 and 5,483,527 includes signal transfer points (STPs) that are connected by special physical links to each of the ATM switch nodes. For call setup, for example, signaling messages are relayed through the signaling system No. 7 (SS#7) network. In such relaying, a non-ATM STP receives the signaling message and advises its associated ATM node of the call setup. The associated ATM node may then identify idle resources to be used for forwarding voice signals to the next ATM node once the



call has been setup, and it may prepare its own signaling message to be used in the relay.

The signaling message for the relay that is prepared by the ATM node is returned to its associated STP, which  
5 forwards the signaling message via the signaling system No. 7 (SS#7) network to another STP associated with the next ATM node. Such relaying continues until the signaling message reaches an STP of an STM local exchange carrier (LEC). Once the call has been set up, the ensuing  
10 speech (or voice-band data) is transported via the ATM nodes. STM/ATM terminal adapters are situated between the STM network and the ATM network for packing samples of voice signals as received from the STM network into ATM cells for application to the ATM network, and for  
15 unpacking ATM cell payloads to obtain voice signals for application to the STM network from the ATM network. The incorporation of ATM into an STM network in the particular manner as described above thus involves a non-ATM

signaling network alongside the ATM nodes. Furthermore,  
each STP node associated with an ATM node performs only  
call control functions in the network of Doshi et al.  
Otherwise and in general, call control and connection  
5 control is traditionally combined in conventional  
communication nodes.

With reference now to FIG. 1A, a conventional unified  
communications node is illustrated at 100. The  
conventional unified communications node 100 may represent  
10 any general purpose switching node in a telecommunications  
network such as a PSTN. Within the conventional  
communications node 100, the call control 105 functions  
and the connection control 110 functions are united. The  
call control 105 and the connection control 110 functions  
15 together encompass the entire seven (7) layers of the Open  
System Interconnection (OSI) protocol. These seven (7)  
layers are denoted as the physical, data link, network,  
transport, session, presentation, and application layers.

Accordingly, the conventional communications node 100 may perform all functions related to both switching intelligence and switching fabric. Conventional communication nodes 100 are not, however, capable of  
5 handling the interworking between (i) narrowband telephony and data communications and (ii) broadband communications using faster and higher bandwidth networks, such as ATM networks.

With reference now to FIG. 1B, a conventional  
10 approach to separating functions of the conventional unified communications node of FIG. 1A is illustrated generally at 150. Conventional approaches attempt to meet the stringent demands of interworking narrowband telephony and data communications with broadband networks using ATM  
15 by separating control functions. Specifically, call control 155 functions are separated from connection control 160 functions. The call control 155 functions are thereby made independent of any particular set of

connection control 160 functions. This separation is typically accomplished by utilizing a conventional communications node (such as the conventional communications node 100 of FIG. 1A) that is stripped of its switching intelligence, leaving only the connection control 160. In effect, a conventional communications node 100 is modified by removing or rendering inoperative the call control 105 functions, thus leaving only the connection control 110 functions. This modified conventional communications node is substituted as the connection control 160 part. The call control 155 part, on the other hand, is typically designed and created without relying on traditional telecommunications hardware or software.

With reference now to FIG. 2, an existing scheme for utilizing a broadband network in conjunction with nodes corresponding to separated functions of a conventional unified communications node is illustrated generally at

200. Switching intelligence 205A,205B parts are connected to switching fabric 210A,210B parts. The switching fabric 210A,210B parts are connected to the ATM network 215, and they effect required emulation and cell packing for interworking a narrowband network (not shown) with the ATM network 215. The switching intelligence 205A,205B parts are usually realized with a UNIX-based server. The switching intelligence 205A,205B parts are intended to provide the advanced calling services and features (e.g., those traditionally provided by the Intelligence Network (IN)). The switching intelligence 205A,205B parts do not include any switching fabric resources, so they must rely on the switching fabric 210A,210B parts for these resources.

Because the switching intelligence 205A,205B parts do not have any of their own switching fabric resources, they are not directly connected to any transport mechanisms, nor do they include the requisite interface(s) for doing

so. Incoming calls are therefore received at a switching fabric 210 part and managed by the associated switching intelligence 205 part. When an incoming call is received at a switching fabric 210 part, call signaling information  
5 is sent to the switching intelligence 205 part. The switching intelligence 205 part performs the appropriate call control functions and sends instructions (e.g., in the form of call signaling information) to the switching fabric 210 part. The switching fabric 210 part follows  
10 the instructions by making the appropriate connections (e.g., to/through the ATM network 215, to/through a narrowband network (not shown), etc.) for forwarding the call data information for the incoming call. As such, no call data information is (or can be) sent to the switching  
15 intelligence 205 part, including from the switching fabric 210 part.

Furthermore, while UNIX-based servers, which realize the switching intelligence 205 parts, may be designed to

operate at high speeds, they suffer from a number of  
deficiencies. First, significant research, design, and  
testing is required to produce appropriate software code  
to run the UNIX-based servers as switching intelligence  
5 205 parts. Existing circuit-switched voice telephony  
networks include many advanced features that require many  
lines of code that have been gradually developed, tested,  
and implemented over many years. Duplicating the diverse  
number and types of features while maintaining the  
10 required level of reliability and service using newly  
written code on a UNIX server is not only a daunting task,  
but it is also virtually impossible to achieve quickly.  
Second, it is extraordinarily difficult to migrate  
gradually from traditional network architectures (e.g.,  
15 those using the conventional unified communications node  
100 of FIG. 1A) to next generation networks that rely on  
broadband transport mechanisms when deploying nodes with  
only the switching intelligence 205 part. System

operators are essentially forced to simultaneously replace whole portions of their networks in large chunks. The consequential large capital expenditures are naturally undesirable to system operators.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222



## SUMMARY OF THE INVENTION

The deficiencies of the prior art are overcome by the methods, systems, and arrangements of the present invention. For example, as heretofore unrecognized, it would be beneficial to re-use and/or extend the life of existing/legacy switches when combining narrowband networks with broadband transport mechanisms. In fact, it would be beneficial to utilize existing switches to enable a gradual migration from narrowband networks to broadband transport mechanisms via the implementation of hybrid switches.

The present invention is directed to a tri-level nodal architecture including a call control node having switching intelligence and narrowband switching fabric, at least one connection control node having broadband switching fabric and an intermediate node for interworking between the call control node and connection control node.

The call control node further includes a load distribution function for distributing the load amongst a plurality of call processors.

In certain embodiments, the load distribution  
5 function assigns the call processors on a per call basis.  
The assigned call processor is used for encoding all  
messages transmitted from the call control node to a  
selected connection control node for the call. In further  
embodiments, a linked call processor has a transport link  
10 towards the selected connection control node, and all  
messages encoded by the assigned call processor are  
transmitted to the selected connection control node  
through the linked call processor. In still further  
embodiments, all messages transmitted from the selected  
15 connection control node to the call control node are  
received and decoded at the linked call processor before  
being transmitted to the call control node through the  
assigned call processor.

In one embodiment, the call control node may be realized by a legacy switch (LS), the intermediate node may be realized by mediation logic (ML) and the LS and ML combined form a media gateway controller (MGC). In addition, the connection control node may be realized by one or more media gateways (MGs).

The above-described and other features of the present invention are explained in detail hereinafter with reference to the illustrative examples shown in the accompanying drawings. Those skilled in the art will appreciate that the described embodiments are provided for purposes of illustration and understanding and that numerous equivalent embodiments are contemplated herein.

## BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the methods, systems, and arrangements of the present invention may be had by reference to the following detailed description  
5 when taken in conjunction with the accompanying drawings wherein:

FIG. 1A illustrates a conventional unified communications node;

FIG. 1B illustrates a conventional approach to  
10 separating functions of the conventional unified communications node of FIG. 1A;

FIG. 2 illustrates an existing scheme for utilizing a broadband network in conjunction with nodes corresponding to separated functions of a conventional  
15 unified communications node;

FIG. 3 illustrates an exemplary schematic view of a hybrid STM/ATM network according to an embodiment of the invention;

FIG. 3A illustrates an exemplary schematic view of selected portions of the hybrid STM/ATM network of FIG. 3, and further showing various operational events;

FIG. 3B illustrates an exemplary schematic view of a hybrid STM/ATM network according to another embodiment of the invention;

FIG. 3C illustrates an exemplary schematic view showing a transit hybrid node pair of the invention connected between two local exchange hybrid node pairs of the invention;

FIG. 3D illustrates a diagrammatic view of an exemplary protocol between two elements of the network of the embodiment(s) of the invention that include hybrid node pairs;

FIGS. 3E, 3F, and 3G illustrate diagrammatic views of alternate exemplary protocols between two elements, a first of the network elements having a hybrid node pair in accordance with embodiment(s) of the invention and a  
5 second of the network elements being an access node with an additional ATM interface having circuit emulation;

FIG. 3H illustrates an exemplary diagrammatic view showing gradual upgrading of a network from a traditional narrowband STM-transported-and-switched environment into  
10 an environment with a hybrid STM/ATM network in accordance with embodiment(s) of the invention;

FIG. 3I illustrates an exemplary schematic view showing a multi-switch hybrid node according to yet another embodiment of the invention;

15 FIG. 4 illustrates another exemplary scheme for utilizing a broadband network in conjunction with nodes having partially separated functions in accordance with the present invention;

FIG. 5 illustrates yet another exemplary scheme for utilizing a broadband network in conjunction with nodes having partially separated functions in accordance with the present invention;

5        FIG. 6 illustrates another exemplary hybrid switch with multiple ports for switching a connection in accordance with the present invention;

10       FIG. 7 illustrates a simplified block diagram of an exemplary hybrid switch in accordance with the present invention;

15       FIG. 8 illustrates exemplary communications and connections between nodes in another simplified block diagram of an exemplary hybrid switch in accordance with the present invention;

20       FIG. 9 illustrates an exemplary method in flowchart form for communicating between nodes in a hybrid switch in accordance with the present invention;

FIGS. 10A-10E illustrate a first set of exemplary traffic scenarios for a hybrid switch in accordance with the present invention;

FIGS. 10F-10K illustrate a second set of exemplary traffic scenarios for a hybrid switch in accordance with the present invention;

FIG. 11 illustrates an exemplary outgoing communication format selection for a hybrid switch in accordance with the present invention;

FIG. 12 illustrates exemplary interactions between a hybrid switch and other telecommunications technology in accordance with the present invention;

FIG. 13 illustrates an exemplary traffic scenario migration for a hybrid switch in accordance with the present invention;

FIG. 14 illustrates an exemplary method in flowchart form for enabling a gradual migration from a primarily



narrowband network to a primarily broadband network in accordance with the present invention;

FIG. 15 illustrates an exemplary tri-level nodal environment in accordance with the present invention;

5        FIG. 15A illustrates a first exemplary tri-level nodal environment alternative in accordance with the present invention;

10       FIG. 15B illustrates a second exemplary tri-level nodal environment alternative in accordance with the present invention;

FIG. 15C illustrates an exemplary interworking function in accordance with the present invention;

15       FIG. 16 illustrates an exemplary tri-level nodal environment implementation in accordance with the present invention;

FIGS. 17A and 17B illustrate two other exemplary tri-level nodal environment implementations in accordance with the present invention;

FIGS. 18A and 18B illustrate two exemplary call setups in an exemplary tri-level nodal environment implementation in accordance with the present invention;

FIG. 19 illustrates exemplary communication path  
5 configuring in an exemplary tri-level nodal network in accordance with the present invention;

FIGS. 20A and 20B illustrate exemplary mapping embodiments in an exemplary tri-level nodal environment implementation in accordance with the present invention;

10 FIG. 21 illustrates an exemplary tri-level nodal environment with exemplary functionality in accordance with the present invention;

FIG. 22 illustrates an exemplary load distribution embodiment in an exemplary tri-level nodal environment  
15 implementation in accordance with the present invention;

FIG. 23 illustrates an exemplary load assignment embodiment in an exemplary tri-level nodal environment implementation in accordance with the present invention;

FIG. 24 illustrates an exemplary message encoding and transmission embodiment in an exemplary tri-level nodal environment implementation in accordance with the present invention;

5        FIG. 25 illustrates an exemplary message decoding and transmission embodiment in an exemplary tri-level nodal environment implementation in accordance with the present invention; and

10        FIGs. 26A and 26B illustrate an exemplary method in flowchart form for transmitting messages between nodes within a tri-level nodal environment in accordance with the present invention.

## DETAILED DESCRIPTION OF THE DRAWINGS

In the following description, for purposes of explanation and not limitation, specific details are set forth, such as particular architectures, interfaces, circuits, information exchanges, logic modules (implemented in, for example, software, hardware, firmware, some combination thereof, etc.), techniques, etc. in order to provide a thorough understanding of the invention. However, it will be apparent to one of ordinary skill in the art that the present invention may be practiced in other embodiments that depart from these specific details. In other instances, detailed descriptions of well-known methods, devices, logical code (e.g., hardware, software, firmware, etc.), etc. are omitted so as not to obscure the description of the present invention with unnecessary detail. It should be understood that the terms "module" and "logic module" as

used herein embrace, subsume, and include, *inter alia*, object oriented programming techniques as well as so-called traditional programming techniques such as, for example, custom-developed applications.

5           Embodiment(s) of the present invention and advantages thereof are best understood by referring to FIGS. 1A-26 of the drawings, like numerals being used for like and corresponding parts of the various drawings.

10           In certain embodiments in accordance with the invention (e.g., including embodiment(s) of the invention of the parent applications), ATM is used as a transport and switching mechanism in a hybrid STM/ATM network, while the signaling remains normal narrowband signaling. The narrowband signaling may be transported on permanent paths  
15           over ATM connections (e.g., permanent virtual connections (PVCs)), and the narrowband speech channels may be transported on ATM and switched on a "per call basis"

(e.g., on-demand) through an ATM switch (e.g., a switched virtual connection (SVC)).

The hybrid STM/ATM network has an access node which services narrowband terminals and which generates a signaling message in connection with call setup. A translator formats the first signaling message into ATM cells so that the first signaling message can be routed through an ATM switch to a circuit switched (e.g., STM) node. The circuit switched node (e.g., PSTN/ISDN) sets up a physical connection for the call and generates a further signaling message for the call, the further signaling message pertaining to the physical connection. The ATM switch routes an ATM-cell-formatted version of the further signaling message to another ATM switch over an ATM physical interface. Thus, the ATM switch switches both narrowband traffic and signaling for the call over the ATM physical interface. The ATM physical interface thus

carries an ATM-cell-formatted version of the further signaling message amidst ATM traffic cells.

In view of the fact that the circuit switched node and the ATM switch employ different parameters (e.g., b-  
5 channel, etc., for the STM node and VP/VC for the ATM switch), in one embodiment the STM node obtains global position numbers (GPN) for use in setting a path for the further signaling message through the ATM switch. In this regard, at the circuit switched node a translation is made  
10 from STM to GPN using an STM/GPN translation table; at the ATM node a translation is made from GPN to VP/VC/port using a GPN/ATM translation table.

The ATM-cell-formatted version of the further signaling message is transported over the ATM physical  
15 link and ultimately reaches a destination access node which serves a destination terminal. A destination translator unpacks ATM cells carrying the ATM-cell-formatted version of the further signaling message to

obtain the STM signaling information for use by the destination access node. The translators may be situated at the access node, for example. In illustrated embodiment(s), the ATM switches are situated at nodes  
5 distinct from the PSTN/ISDN nodes, but such need not be the case in other embodiment(s). The signaling messages can be in accordance with the signaling system no. 7 (SS#7) convention, and the further signaling message can be one of an ISUP or a TUP message, for example.

10 Referring now to FIG. 3, an exemplary hybrid STM/ATM network 320 according to an embodiment of the invention is illustrated. Narrowband terminal devices communicate with hybrid STM/ATM network 320 through access nodes, such as access node 322<sub>o</sub> and access node 322<sub>d</sub>. For example, FIG.  
15 3 shows terminals 324<sub>o</sub> connected to access node 322<sub>o</sub>, particularly ISDN terminal 324<sub>o-I</sub> and PSTN terminal 324<sub>o-P</sub>. Similarly, access node 322<sub>d</sub> has access terminals 324<sub>d</sub> connected thereto, namely ISDN terminal 324<sub>d-I</sub> and PSTN



terminal 324<sub>D-P</sub>. Of course, a differing (and most likely greater) number of terminals can be connected to each access node 322, but for simplicity only two such terminals are shown for exemplary purposes in FIG. 3. It  
5 should be noted that, as used herein, the term "access node" is not limited to a simple node used merely for connecting subscriber lines, for it may encompass other nodes such as a local exchange (LE) node, for example.

The hybrid STM/ATM network 320 of FIG. 3 comprises  
10 one or more STM nodes, also known as PSTN/ISDN nodes 330. While only two such PSTN/ISDN nodes 330<sub>1</sub> and 330<sub>2</sub> are shown in FIG. 3 for sake of illustration, it should be understood that the invention is not limited to only two such nodes. The structure and operation of conventional  
15 PSTN/ISDN nodes 330 are well known; such as those typified by utilization of Ericsson AXE switches, for example. Therefore, only selected pertinent portions of conventional PSTN/ISDN nodes 330 are described herein with

reference to PSTN/ISDN node 330<sub>1</sub>. For example, PSTN/ISDN  
node 330<sub>1</sub> has processor(s) 332 which execute, e.g., node  
application software including switch and resource control  
software 333. Such software is used to control STM  
5 circuit switch 335 as well as signaling terminals 337  
which comprise PSTN/ISDN node 330<sub>1</sub>. Other details of the  
structure and operation of a conventional PSTN/ISDN node  
are understood, for example, from United States Patent  
Application Serial No. 08/601,964 for "Telecommunications  
10 Switching Exchange", which is hereby incorporated by  
reference in its entirety herein.

The STM/ATM network 320 of certain embodiment(s) of  
the invention is considered a hybrid network in view of  
the fact that ATM nodes 340 are also included therein. As  
15 explained hereinafter, the ATM nodes 340 are used not only  
to route narrowband traffic between access nodes 322, but  
also for transport of signaling in ATM cells over an ATM  
physical interface. In the illustrated example, the ATM

network aspect includes two exemplary ATM nodes, particularly ATM node 340<sub>1</sub> and ATM node 340<sub>2</sub>, which are connected by ATM physical interface or link 341. Again, it should be understood that the ATM component can (and typically does) comprise a greater number of ATM nodes, with the nodes being connected by ATM physical links.

In hybrid network 320, a PSTN/ISDN node 330 and a ATM node 340 can be paired together in the manner illustrated in FIG. 3. With such a pair, the PSTN/ISDN node 330 and ATM node 340 are collectively referred to as hybrid node pair 330/340. The network 320 of certain embodiment(s) of the invention thus can comprise any number of hybrid node pairs 330/340. An ATM node such as ATM node 340 takes on differing configurations, but commonly has a main processor 342 or the like which executes application software including switch and resource control software as generally depicted by 343 in FIG. 3. The heart of an ATM node is usually the ATM switch core or switch fabric,

which for the illustrated embodiment is shown as ATM cell switch 345 in FIG. 3. Further information regarding an exemplary ATM switch is provided by United States Patent Application Serial No. 08/188,101, entitled "Asynchronous  
5 Transfer Mode Switch", filed November 9, 1998, which is hereby incorporated by reference in its entirety herein. ATM cell switch 345 has plural ingress ports and plural egress ports, with at least some of such ports having a device board attached thereto.

10 Each device board at ATM node 340 can have one or more different functions performed thereby or one or more different devices mounted thereon. For example, one of the device boards attached to a port of ATM cell switch 345 can, in one embodiment, have the main processor 342  
15 mounted thereon. Other device boards may have other processors, known as "board processors". Some device boards serve as extension terminals (ETs) 346 which may be used to connect the ATM node to other nodes. For example,

the ATM physical link 341 shown in FIG. 3 has a first end connected to an extension terminal ET 346<sub>1</sub> of ATM node 340<sub>1</sub>, while a second end of ATM physical link 341 is connected to an unillustrated extension terminal ET of ATM node 340<sub>2</sub>. The device boards connected to ATM cell switch 345 of ATM node 340 are not specifically illustrated in detail in FIG. 3, but the structure and operation of such device boards is understood with reference to (for example) the following United States Patent Applications, all of which are hereby incorporated by reference in their entirety herein: U.S. Patent Application Serial No. 08/893,507 for "Augmentation of ATM Cell With Buffering Data"; U.S. Patent Application Serial No. 08/893,677 for "Buffering of Point-to-Point and/or Point-to-Multipoint ATM Cells"; U.S. Patent Application Serial No. 08/893,479 for "VPNC Look-Up Function"; U.S. Patent Application Serial No. 09/188,097 for "Centralized Queuing For ATM Node", filed November 9, 1998.

As explained hereinafter, signaling (e.g., for call setup) is routed from an access node 322 through an ATM node 340 to an appropriate one of the PSTN/ISDN nodes 330. Such being the case, a circuit emulation or translator 350 is provided for each access node 322 which communicates with an ATM node 340. The translators 350 serve, e.g., to encapsulate signaling information from the access node 322 into ATM cells for signaling directed toward an ATM node 340, and conversely unpack ATM payloads received from an ATM node 340 to extract signaling information for use by the access node 322. In this particular illustrated embodiment, the translators 350 are preferably provided at or proximate to their associated access nodes 322. That is, translator 350<sub>o</sub> may be situated at or included in access node 322<sub>o</sub>; translator 350<sub>p</sub> may be situated at or included in access node 322<sub>p</sub>. A pair of physical links, shown as links 351, are provided for connecting each

access node 322 to a corresponding one of the ATM nodes 340.

ATM node 340 is connected to a PSTN/ISDN node 330 by a physical link 360. With reference to ATM node 340<sub>1</sub>, for example, a pair of switch-to-switch links 360 is employed to connect ATM cell switch 345 (through its circuit emulation board 370) to STM circuit switch 335 of PSTN/ISDN node 330, for the carrying of signaling messages. One of the links in pair 360 carries messages from ATM cell switch 345 (after translation at circuit emulation board 370) to STM circuit switch 335; the other link of the pair 360 carries messages in the reverse direction.

In the illustrated embodiment, a dedicated VPI, VCI internal to ATM cell switch 345 is used for signaling. Thus, with reference to ATM node 340<sub>1</sub>, for example, link 351<sub>0</sub> is connected to extension terminal (ET) 346<sub>2</sub>, which in turn is connected to a first pair of dedicated ports of

ATM cell switch 345. Signaling messages received at ATM  
node 340<sub>1</sub> which are destined to PSTN/ISDN node 330<sub>1</sub> are  
routed on the dedicated internal VPI/VCI to a port of ATM  
cell switch 345 which ultimately connects (via circuit  
5 emulator 370) to switch-to-switch links 360. However,  
since the signaling routed through ATM cell switch 345 is  
encapsulated in ATM cells, a translation to the STM  
signaling must be performed prior to transmitting the  
signaling information on switch-to-switch links 360. For  
10 this reason, a device board connected to switch-to-switch  
links 360 has the circuit emulation (CE) or translator 370  
mounted thereon.

The circuit emulation (CE) or translator 370 serves  
to unpack signaling information which is destined to  
15 PSTN/ISDN node 330, but contained in ATM cells, so that  
the signaling information can be extracted from the ATM  
cells prior to application on switch-to-switch links 360.  
Conversely, signaling information received from PSTN/ISDN



node 330<sub>1</sub> on switch-to-switch links 360 at translator 370 is encapsulated into ATM cells for routing through ATM node 340<sub>1</sub>. From FIG. 3 it can also be seen that a plurality of interfaces 300a-300f are utilized in the hybrid STM/ATM network 320 of certain embodiment(s) of the invention. These interfaces are described below, primarily with reference to the exemplary nodes (e.g., PSTN/ISDN node 330<sub>1</sub> and ATM node 340<sub>1</sub>).

Interface 300a is a logical interface which exists between processor(s) 332 of PSTN/ISDN node 330<sub>1</sub> and main processor(s) 342 of ATM node 340<sub>1</sub>. Interface 300a enables PSTN/ISDN node 330 to control the ATM node 340 connected thereto. That is, with the signaling carried by interface 300a, PSTN/ISDN node 330<sub>1</sub> can order physical connections which are to be set up in ATM node 340<sub>1</sub>. Interface 300a can be a proprietary interface or an open interface (such as a General Switch Management Protocol (GSMP) interface [see Request For Comments (RFC) 1987]). Logical interface 300a

can be carried on any physical interface, such as interface 360 described below. Alternatively, interface 300a can be carried by a separate link (e.g., between processors 332 and 342), or carried on top of IP/Ethernet  
5 links.

Interface 300b is the signaling between the PSTN/ISDN nodes 330 and the access node 322 connected thereto. Interface 300b is carried on one or more semipermanent connections through the STM circuit switch 335; through  
10 the interworking unit with circuit emulation 370 into ATM cell switch 345; and over permanent virtual connections to access node 322 (particularly to translator 350 in access node 322, where it is emulated back and terminated). As mentioned above, translator 350 is employed to encapsulate  
15 the narrowband signaling from an access node 322 in ATM cells for use by an ATM node 340, and conversely for unpacking ATM cells with signaling information for use by

an access node 322. Each STM channel on the user side may have a corresponding VPI/VCI on interface 300b.

Interface 300c is the non-broadband signaling that is carried through and between the nodes. Interface 300c thus carries the normal signaling system No. 7 (SS#7) interface (e.g., TUP or ISUP) which is transparently carried in ATM-cell-formatted versions of signaling messages over ATM physical link 341. In PSTN/ISDN node 330, the signaling terminals 337 are used for common channel signaling. In at least one embodiment, signaling terminals 337 can be pooled devices situated at STM circuit switch 335. Alternatively, the signaling terminals 337 can be connected directly to the interfaces between the STM and ATM switches.

Interface 300d is the physical interface provided by switch-to-switch link 360. Interface 300d can be used to carry speech for a call to and from an STM network, and also to carry the signaling of interface 300b and

interface 300c as described herein. In addition,  
interface 300d can also be used to link-in special  
equipment that is to be connected to a normal circuit  
switch (e.g., conference equipment, answering machines,  
5 etc.). Interface 300d can be realized by any standard  
physical media, such as E1, for example; it being  
understood that STM-1 or similar speeds may be suitable.  
The physical interface 300d can also carry the voice data  
for a conversation between any of the terminals shown in  
10 FIG. 3 and an unillustrated terminal connected to the  
circuit switched network, in which situation the hybrid  
node pair 330/340 acts as a gateway.

Interface 300e is the ATM physical link 341 to other  
ATM nodes. Any standard link for ATM may be employed for  
15 interface 300e. A dedicated VP/VC is employed to  
transparently transfer the signaling system no. 7 (SS#7)  
signaling between PSTN/ISDN nodes 330 over interface 300e.  
Interface 300f, shown in FIG. 3 as connecting each access

node 322 with its terminals, is a typical user-network interface (e.g., ISDN, BA/BRA, PRA/PRI, two-wire PSTN, etc.).

For two traditional circuit switched PSTN/ISDN nodes  
5 to communicate with one another using protocols such as  
ISUP or TUP, it is preferable that ISUP entities in both  
PSTN/ISDN nodes have coordinated data tables. In this  
regard, each of the two PSTN/ISDN nodes has a table which  
translates a CIC value onto a same timeslot in a same  
10 physical interface connecting the two PSTN/ISDN nodes.  
Thus, a CIC value (together with a point code) represents  
a particular timeslot on a particular physical link. One  
specific CIC preferably points out the same time slot in  
the tables of both PSTN/ISDN nodes. In other words, the  
15 data tables of the two PSTN/ISDN nodes are preferably  
coordinated.

The need to coordinate the data tables of PSTN/ISDN  
node 330<sub>1</sub> and PSTN/ISDN node 330<sub>2</sub> for ISUP/TUP similarly

exists in certain embodiment(s) of the invention. If two hybrid nodes  $330_1/340_1$  and  $330_2/340_2$  have a communication channel set up between them, by means of a semipermanent connection carrying SS#7 signaling for example, the translation tables 339 in both hybrid nodes are preferably coordinated from the standpoint of using CIC. This typically means that in both hybrid nodes  $330_1/340_1$  and  $330_2/340_2$  a certain CIC points at the same VP and VC (and possibly AAL2 pointer) identifying cells on a certain physical link (e.g., link 341) connecting the two hybrid nodes. Alternatively, the same objective may be accomplished by other suitable means such as a cross-connected-ATM switch positioned between the hybrid nodes that switches packets and gives the packets the VP and VC value understood by the other node.

Referring now to FIG. 3A, an exemplary structure of hybrid STM/ATM network 320, having omitted therefrom various items including the interfaces, is illustrated.

FIG. 3A also provides an example of signal processing for a call originating at terminal 324<sub>O-P</sub> for which the called party number (destination) is terminal 324<sub>D-P</sub>. As shown by the arrow labeled E-1, at event E-1 a SETUP message is sent from terminal 324<sub>O-P</sub> to access node 322<sub>O</sub>. In the illustrated embodiment, the SETUP message is an IAM message for an ISUP network interface, and is for a 30B+D PRA and for VS.x carried on a 64 kb/s bit stream in a circuit switched timeslot.

At the translator 350<sub>O</sub> associated with the access node 322<sub>O</sub>, at event E-2 the signaling from terminal 324<sub>O-P</sub> is converted from STM to ATM by packing the signaling information into ATM cell(s). In this regard, after the circuit emulation a table is employed to translate from a 64 kb/s speech channel from terminal 324<sub>O-P</sub> to a corresponding ATM address (VP/VC). The signaling of the SETUP message, now encapsulated in ATM cell(s), is applied to link 351<sub>O</sub> and transmitted to ATM cell switch 345 of ATM

node 340<sub>1</sub> as indicated by event E-3. As further indicated  
by event E-4, the ATM cell(s) containing the SETUP message  
signaling is routed through the ATM cell switch 345 in  
accordance with a switch internal VP/VC dedicated for STM-  
5 originated signaling. Upon egress from ATM cell switch  
345, the signaling information for the SETUP message is  
retrieved from the ATM cell(s) by translator 370 (event E-  
5), and it is reconverted at translator 370 from ATM to  
STM format, so that the SETUP message signaling  
10 information can be applied in STM format at event E-6 to  
switch-to-switch link 360. The SETUP message, now again  
in STM format, is routed through STM circuit switch 335  
(as indicated by event E-7) to an appropriate one of the  
signaling terminals 337. Upon receipt of the SETUP  
15 message signaling information at the appropriate signaling  
terminal 337, the signaling information is forwarded to  
processor(s) 332 of PSTN/ISDN node 330, which engage in  
STM traffic handling (as indicated by event E-8).



In its traffic handling, the processor 332 of PSTN/ISDN node 330 realizes that the incoming side of the call and the outgoing side of the call have physical connections through an ATM node. In this regard, when the  
5 access points of the connection were defined (subscriber or network interface), a bearer type was associated with the connection and stored in application software. In the present scenario, when the SETUP message (e.g., an IAM message in the case of an ISUP network interface) was  
10 received at PSTN/ISDN node 330, the stored bearer type data was checked in order to determine what switch was on the incoming side to PSTN/ISDN node 330. Further, the bearer type data stored for the outgoing point (e.g., based on B-Subscriber number) is similarly checked, and if  
15 the stored data indicates that both incoming and outgoing sides have an ATM bearer, the PSTN/ISDN node 330 can conclude that ATM node 340 is to be operated (e.g., utilized). In addition, data received in the SETUP

message (particularly the B-subscriber number) is analyzed to determine that the called party (destination) terminal 324<sub>D-P</sub> can be reached by contacting PSTN/ISDN node 330<sub>2</sub>. The PSTN/ISDN node 330<sub>1</sub> realizes that it has an SS#7  
5 signaling interface 300c to PSTN/ISDN node 330<sub>2</sub>, and therefore selects a free CIC (e.g., a CIC not used by any other call) for use toward PSTN/ISDN node 330<sub>2</sub>.

If, on the other hand, the stored bearer type data had indicated an STM bearer, both PSTN/ISDN node 330 and  
10 ATM node 340 have to be operated. Thus, PSTN/ISDN node 330 and ATM node 340 collectively function as a gateway between the STM and ATM worlds. Upon realizing that further signaling for the call will be routed through ATM nodes, in the embodiment(s) of the invention shown in FIG.  
15 3 and FIG. 3A, the PSTN/ISDN node 330<sub>1</sub> makes reference to an STM/GPN translation table 339 maintained by processor(s) 332 (see event E-9). Two translations are performed using the STM/GPN translation table 339. As a

first translation, the information (e.g., b-channel and access information in the case of ISDN or CIC plus signaling system #7 point codes in the case of PSTN) contained in the SETUP message is translated to a global position number (GPN). As a second translation, the CIC and destination point code for a circuit leading to hybrid node pair 330/340 is translated to another global position number (GPN).

In connection with the foregoing, the global position number (GPN) is a common way to identify the connection points, and as such is understood by the pair of nodes (PSTN/ISDN node 330 and ATM node 340). In other words, the GPN is an address, or reference, or system internal pointer known by both PSTN/ISDN node 330 and ATM node 340, and used to translate between port/VP/VC and circuit switch address. Usage of GPN in the embodiment of FIG. 3 and FIG. 3A thereby obviates the sending of real addresses between PSTN/ISDN node 330 and ATM node 340.

Advantageously, GPN can be shorter, meaning that there is less data to send. For traditional PSTN, the GPN uniquely corresponds to the 64 kbit voice on a two-wire line, but for ISDN, the GPN corresponds to a b-channel (which may be  
5 used by several subscribers).

Then, as event E-10, the PSTN/ISDN node 330 generates an ATM switch control message intended to setup a physical connection in ATM node 340. This message of event E-10 contains the two global position numbers (GPNs) obtained  
10 from STM/GPN translation table 339 at event E-9, together with an order for the ATM node 340 to connect the two GPN addresses in ATM switch fabric 345. The PSTN/ISDN node 330 sends the switch control message generated at event E-10 to processor 342 of ATM node 340 over interface 300a,  
15 as shown by event E-11.

Upon reception of the switch control message sent as event E-11 to ATM node 340<sub>1</sub>, as indicated by event E-12, main processor 342 consults GPN/ATM translation table 349

in order to translate the two global position numbers (GPNs) contained in the event E-10 switch control message into VP/VC/port information understood by ATM node 340<sub>1</sub>. That is, the two global position numbers (GPNs) are used  
5 to obtain VP/VC/port information for ultimately reaching both the origination terminal (324<sub>O-P</sub>) and the destination terminal (324<sub>D-P</sub>). Upon successful translation of GPN to ATM, and assuming sufficient resources, processor 342 of ATM node 340<sub>1</sub> sets up a path through ATM Switch 345 and  
10 reserves resources on the port (trunk or link 341) for the call from terminal 324<sub>O-P</sub> to terminal 324<sub>D-P</sub>. The path set up and resource reservation activities are accomplished using switch/reservation control 343 and are collectively illustrated as event E-13 in FIG. 3.

15 Since PSTN/ISDN node 330 preferably knows whether ATM node 340<sub>1</sub> was successful in performing a GPN/ATM translation, a successful translation message is sent over interface 300a as event E-14 from ATM node 340<sub>1</sub> to

PSTN/ISDN node 330<sub>1</sub>. If the GPN/ATM translation is not successful at ATM node 340<sub>1</sub>, or if there are no available resources at ATM node 340<sub>1</sub>, a call rejection message is sent back to the originating terminal. After PSTN/ISDN  
5 node 330 receives the confirmatory message of event E-14 (that ATM switch 345 has been setup and link reservations made (in accordance with event E-13)), at event E-15 the PSTN/ISDN node 330<sub>1</sub> prepares and sends its further signaling message (e.g., ISUP or TUP) toward the PSTN/ISDN  
10 node at the other end (e.g., PSTN/ISDN node 330<sub>2</sub>). This further signaling message is shown as event E-15 in FIG. 3A. The signaling of event E-15 (e.g., an ISUP or TUP message) includes a message transfer part (MTP), and can be sent out on a timeslot (e.g., 64 kb/s) which carries  
15 the SS#7 signaling.

As the signaling of event E-15 arrives at ATM node 340<sub>1</sub>, the ATM node 340<sub>1</sub> prepares its ATM cell-formatted version of the signaling. In particular, the translator

370 puts the signaling information of the signaling of event E-15 into the payload of one or more ATM cells. For example, the translator 370 is configured to take the 64 kb/s signaling information bit stream and to pack it into  
5 ATM cells with a predefined VP, VC, and a physical port. As also indicated as event E-15, the ATM cell-formatted version of the further signaling message is routed through ATM cell switch 345 and onto a link indicated by the VP/VC/port information obtained from the translation. In  
10 particular, in FIG. 3A the ATM cell-formatted version of the further signaling message is transported on ATM physical link 341, as shown by event E-16.

Upon reaching ATM node 340<sub>2</sub>, the ATM cell-formatted version of the further signaling messages obtains a new  
15 internal VPI/VCI for the ATM cell switch 345 of ATM node 340<sub>2</sub>, and is routed (as indicated by event E-17) through ATM cell switch 345 of ATM node 340<sub>2</sub> to a circuit emulator (not explicitly shown) in ATM node 340<sub>2</sub>, which is analogous

to circuit emulator 370 in ATM node 340<sub>1</sub>. The circuit emulator of ATM node 340<sub>2</sub> performs the conversion from ATM to STM format in like manner as circuit emulator 370 in ATM node 340<sub>1</sub>, and then passes the signaling message to  
5 PSTN/ISDN node 330<sub>2</sub> as event E-18.

In PSTN/ISDN node 330<sub>2</sub>, the ISUP message is received together with the CIC value (from the message transfer part (MTP)) and the B-subscriber number (which is included in the ISUP message). As indicated by event E-19, the  
10 second hybrid node 330<sub>2</sub>/340<sub>2</sub> also performs an analysis of the B-subscriber number and concludes that the B-subscriber number is associated with terminal 324<sub>D-P</sub>, which involves B channels. The PSTN/ISDN node 330<sub>2</sub> then selects a B-channel which can be used to reach terminal 324<sub>D-P</sub>, or  
15 negotiates with the terminal 324<sub>D-P</sub> as to which B-channel to use (depending on the terminal type and protocol type ISDN or PSTN). The PSTN/ISDN node 330<sub>2</sub> also signals terminal 324<sub>D-P</sub> to activate a ringing signal (as indicated



by event E-20). When an answer is received from terminal 324<sub>D-P</sub> (or during or before receiving an answer), the PSTN/ISDN node 330<sub>2</sub> consults its STM/GPN translation table 339 (not explicitly shown) using a CIC value and a B-  
5 channel. The PSTN/ISDN node 330<sub>2</sub> then operates the ATM switch 345 (not explicitly shown) of ATM node 340<sub>2</sub> in the same manner as described for ATM node 340<sub>1</sub>, as indicated by event E-21.

Operation of ATM switch 345 of ATM node 340<sub>2</sub> allows  
10 in-band data (e.g., voice data) carried in ATM packets to be passed through the ATM switch. Such operation is accomplished in like manner as described previously hereinabove (e.g., by consulting a table such as table 339, by sending an ATM switch control message, by  
15 consulting a table such as table 349, and by setting up of a path in the ATM switch). When an ATM switch is operated as described above, the resulting path through both ATM switches (carrying in-band information) has to be set up

in the same way at both ends. This implies that encapsulation of in-band information (which is controlled by circuit emulation (e.g., circuit emulation 370)) at the two end points of the path is preferably set up in the same way. To minimize delay, AAL2 is preferably utilized by circuit emulation 370 for the encapsulation, although other types of protocols may be alternatively used.

As noted hereinabove, a bearer type is associated with a connection and stored in the application software of the PSTN/ISDN node 330. It is presumed that the PSTN/ISDN node 330 already is able to handle traditional access points (subscriber or network interfaces) connected to STM circuit switches. In so doing, the PSTN/ISDN node 330 has logical representations of these existing access points in a static data structure of the PSTN/ISDN node 330. In accordance with certain embodiment(s) of the invention, the PSTN/ISDN node 330 additionally handles access points connected to the ATM switch. In this

regard, see (for example) interface 341 of FIG. 3C  
(hereinafter described). Thus, for certain embodiment(s)  
of the invention, the PSTN/ISDN node 330 has logical  
representations of these additional access points in its  
5 static data structure. Therefore, the bearer type data  
may be employed in the prior discussion as a way of  
distinguishing the logical representation of the  
additional access points (e.g., ATM-related access points)  
in the static data structure from the logical  
10 representation of the traditional access points.

It was also noted hereinabove that encapsulation of  
in-band information is preferably set up the same way at  
both ends. More specifically, a same type of cell filling  
is preferably employed by two circuit emulation devices  
15 that are connected together. For example, if on a link  
connecting two circuit emulation devices an ATM cell is  
packed with only one voice sample by a first of the  
circuit emulation devices, the second of the circuit

emulation devices preferably packs ATM cells in a similar manner. Alternatively, another emulation and/or bridging mechanism or scheme may be employed.

5 In the above regard, filling only part of an ATM cell with information is a technique for reducing delays, although it may increase overhead. Another way of reducing delay is employment of the AAL2 protocol. As understood by those skilled in the art, AAL2 is a protocol layer on top of ATM, and it allows transport of mini-cells  
10 within ATM cells. Usage of the smaller AAL2 cells helps address bandwidth and delay problems in the air interface. Certain embodiment(s) of the invention may be utilized with AAL2 switching as an alternative to ATM switching. If one implements AAL2 in certain embodiment(s) of the  
15 invention, the switch 345 operates as an AAL2 switch and GPN/ATM translation table 349 in ATM node 340 preferably also includes an AAL2 pointer. Whenever the ingress and egress point is referenced, it can alternately include an

AAL2 pointer. Thus, as used herein and in the appended claims, ATM encompasses ATM-related protocols on top of ATM, such as AAL1, AAL2, AAL5, etc. It should also be understood that the term "broadband", as used herein and  
5 in the appended claims, embraces and encompasses packet-switched technologies in general (e.g., IP, VoIP, Frame-relay, ATM, etc.).

Referring now to FIG. 3B, an exemplary hybrid STM/ATM network 320' according to another embodiment of the invention is illustrated. The embodiment of FIG. 3B  
10 primarily differs from the embodiment of FIG. 3 in that the embodiment of FIG. 3B does not employ global position numbers (GPNs). Rather, the embodiment of FIG. 3B uses an ATM/STM translation table 339' in processor 332 of  
15 PSTN/ISDN node 330<sub>1</sub> instead of an GPN/ATM translation table. In the embodiment of FIG. 3B, the translation tables in the circuit emulation 350<sub>0</sub> translate the SETUP message from a 64 kb/s speech channel to an ATM address

(VP and VC) in a manner similar to that of event E-2 in the embodiment(s) of FIG. 3 and FIG. 3A. After routing of the translated SETUP message through ATM switch 345<sub>1</sub>, the circuit emulation 370 translates the SETUP message to the STM format as occurred at event E-5 of the embodiment(s) of FIG. 3 and FIG. 3A.

The embodiment of FIG. 3B also differs from that of the embodiment(s) of FIG. 3 and FIG. 3A in that processor 332 of PSTN/ISDN node 330 terminates the narrowband signaling by translating a narrowband reference point (e.g., b-channel if an ISDN connection) to a corresponding ATM address for use by ATM node 340. Thus, for the FIG. 3B embodiment, the switch control message of event E-11 sends the ATM VP/VC/port information understood by ATM node 340<sub>1</sub>. Thus, the translation of event E-12 of the FIG. 3/FIG. 3A embodiment is unnecessary in the FIG. 3B embodiment. Rather, upon receiving the ATM VP/VC/port information in the switch control message of event E-11,

the embodiment of FIG. 3B proceeds to the path set up and resource reservation operations denoted as event E-13.

The principles as illustrated in the embodiments hereof are also applicable to the carrying of other types of signaling messages in ATM cells. Included among such  
5 other types of signaling messages are those destined for the originating terminal (e.g., a call completion signaling message), in which case some of the events described herein are performed essentially in reverse  
10 order.

Referring now to FIG. 3C, an exemplary illustration of how hybrid node pairs 330/340 of the invention may be arranged in an exemplary hybrid STM/ATM network 320" is presented. Network 320" has three node pairs 330/340,  
15 including a transit exchange hybrid node pair 330/340<sub>TX</sub> between two local exchange hybrid node pairs 330/340<sub>1</sub> and 330/340<sub>2</sub>. FIG. 3C shows provision of a "#7 signaling system" 393, which is a logical system carried in the ATM

network on an ATM AAL layer as described above. As an alternative embodiment, the "#7 signaling system" 393 may be provided with its own physical network.

Referring now to FIG. 3D, a diagrammatic view of an exemplary protocol usable between two elements of a network in accordance with embodiment(s) of the invention that include hybrid node pairs is illustrated. The ATM node 340 with its ATM switch 345 terminates the ATM and AAL1 (circuit emulation part) layers; the PSTN/ISDN node 330 terminates the MTP and ISUP layers.

Referring now to FIGS. 3E, 3F, and 3G, diagrammatic views of alternate exemplary protocols between two elements, a first of the network elements having a hybrid node pair in accordance with embodiment(s) of the invention, and a second of the network elements being an access node with an additional ATM interface with circuit emulation is illustrated. In the first network element, the ATM switch 345 terminates the ATM and AAL1 (circuit



emulation part) layers, while the layers above are terminated by the PSTN/ISDN node 330. In the second network element, the ATM interface and circuit emulation addition to the access node terminates the ATM and AAL1  
5 layers, while the layers above are terminated by the connected terminal and the access node part. The exemplary protocols of FIGS. 3E, 3F, and 3G can be used, for example, on the interface 300b.

Referring now to FIG. 3H, an exemplary gradual  
10 upgrade of a network from a traditional narrowband STM-transported-and-switched environment into the environment (e.g., hybrid STM/ATM network 320) of certain embodiment(s) of the invention is illustrated. In FIG. 3H, the circuit emulation equipment (translator) 395  
15 separates the hybrid environment from the pure STM environment. If node B (PSTN/ISDN node 330<sub>N+1</sub>) is upgraded with ATM switching and (signaling and traffic) transport according to certain embodiment(s) of the invention, the

node C (PSTN/ISDN node 330<sub>N+2</sub>) is not disturbed if the circuit emulation equipment (translator) 395 is moved in between nodes B and C in the manner illustrated by the dotted-dashed line 396 as shown in FIG. 3H.

5 Referring now to FIG. 3I, certain embodiment(s) of the invention permit the possibility of one logical node to include many switches, with switching logic within the node coordinating the setting up of paths through the switches. This logic also inserts interworking functions  
10 (IWFs) between switches (if needed), and makes it possible to use resources independent on which switch they are allocated to. For example, the multi-switch node 397 of certain embodiment(s) of the invention includes the PSTN/ISDN node 330 with its STM switch 335, connected by  
15 interface 300d to ATM node 340<sub>7-1</sub>. Specifically, connection is made through IWF 344<sub>7-1</sub> to ATM switch 345<sub>7-1</sub> of ATM node 340<sub>7-1</sub>. The ATM switch 345<sub>7-1</sub> of ATM node 340<sub>7-1</sub> is connected by interface 300e to an ATM network, as well as to ATM

node 340<sub>7-2</sub> and ATM node 340<sub>7-3</sub> included in the multi-switch  
node 397. The ATM node 340<sub>7-2</sub> has a switch 345<sub>7-2</sub> and an IWF  
344<sub>7-2</sub>, through which connection can be made with access  
node 322<sub>7-1</sub>. The ATM node 340<sub>7-3</sub> has an ATM AAL2 switch  
5 345<sub>7-3</sub>, which connects to ATM nodes 340<sub>7-1</sub> and 340<sub>7-2</sub> through  
IWF 344<sub>7-3</sub> of ATM node 340<sub>7-3</sub>. Access nodes 322<sub>7-2</sub> and 322<sub>7-3</sub>  
are connected to ATM AAL2 switch 345<sub>7-3</sub> of ATM node 340<sub>7-3</sub>.

Certain embodiment(s) of the invention advantageously  
reuse PSTN and ISDN software in the PSTN/ISDN nodes 330 in  
10 a fairly simple way. That is, already-developed  
narrowband application software residing in the PSTN/ISDN  
nodes 330 can be utilized, while on-demand ATM connections  
are used as traffic bearers. The invention thus allows a  
PSTN/ISDN node such as PSTN/ISDN node 330 to control the  
15 call, which facilitates use of well-proven software for  
various services and functions (e.g., subscriber services,  
intelligent network (IN) services, Centrex, Charging  
Customer Care systems, etc.).

ATM is thus used as a transport and switching mechanism in certain embodiment(s) of the invention, while the signaling remains normal narrowband signaling. The narrowband signaling is transported on permanent paths  
5 over ATM connections, and the narrowband speech channels are transported on ATM, and switched on a "per call basis" (e.g., on-demand) through an ATM switch.

The narrowband application software executed by processor(s) 332 of PSTN/ISDN nodes 330 thus acts as if  
10 operating on its STM circuit switched transport, when in fact it is actually operating on an ATM cell switch. It should be understood that the ATM switch may reside in a separate ATM node or may be integrated in the same node as the STM switch. On a "per call basis", the switching  
15 logic in the PSTN/ISDN nodes 330 requests the switching mechanism in the ATM nodes 340 to be set up and disconnected through an ATM cell switch.

It should be understood that variations of the foregoing are within the scope of the embodiments of the invention. For example, the circuit emulation 370 is shown (e.g., in FIG. 3) as being provided on a device  
5 board of ATM node 340. Alternatively, circuit emulation 370 may be located elsewhere, such as (for example) on link 360 between PSTN/ISDN node 330 and ATM node 340, or even included in PSTN/ISDN node 330 (e.g., at either end of interface 300d). While various processors, such as  
10 processors 332 and 342, have been illustrated as single processors, it should be understood that the functionality of such processors may be situated or distributed in different ways (e.g., distributed over several processors to achieve, e.g., scalability in respect to processing  
15 capacity and reliability), for example.

In the foregoing examples, the SETUP message (received at the STM node in STM format) is routed through STM circuit switch 335 as indicated by the event E-8 to

signaling terminals 337. It should be understood, however, that depending upon implementation in an PSTN/ISDN node, signaling may take another way to reach a signaling terminal (e.g., other than through a switch).

5 The invention also describes a system with one STM switch and one ATM switch associated with one another. This particular configuration is advantageous in that resources which take care of certain kinds of signals (e.g., in-band signals) may be situated in the STM switch and be used  
10 also for the ATM transported calls. This is also a way of reusing the installed base, if such exists. Also, certain embodiment(s) of the invention can perform switching on various levels, such as the AAL2 level and with mini-cells, which tends to reduce any delay/echo problems.

15 The invention thus pertains to the telecommunications world and an attempt to introduce ATM to a telecommunications network. The invention addresses the situation in which a circuit switched telephony network

pre-exists, and it is to be augmented or partially replaced by parts that employ ATM for transport and switching. Certain embodiment(s) of the invention need not employ broadband signaling, but rather narrowband  
5 signaling with the bearer part of the call following the signaling to the same extent as in a traditional narrowband circuit switched network.

As described herein, ATM may be used as a transport and switching mechanism in a hybrid STM/ATM network, while  
10 the signaling remains normal narrowband signaling. The narrowband signaling may be transported on permanent paths over ATM connections, and the narrowband speech channels may be transported on ATM and switched on a "per call basis" (e.g., on-demand) through an ATM switch. The  
15 hybrid STM/ATM network may include an access node that services narrowband terminals and which generates a signaling message in connection with call setup. A translator formats the first signaling message into ATM

cells so that the first signaling message may be routed through an ATM switch to a circuit switched (e.g., STM) node. The circuit switched node (e.g., PSTN/ISDN) sets up a physical connection for the call and generates a further signaling message for the call, the further signaling message pertaining to the physical connection. The ATM switch routes an ATM cell-formatted version of the further signaling message to another ATM switch over an ATM physical interface. Thus, the ATM switch switches both narrowband traffic and signaling for the call over the ATM physical interface.

Referring now to FIG. 4, another exemplary scheme for utilizing a broadband network in conjunction with nodes having partially separated functions in accordance with the present invention is illustrated generally at 400. The nodes 405A,405B are connected to the nodes 410A,410B. The nodes 405A,405B each include both call control functions and connection control functions. In effect,



each of the nodes 405A,405B (e.g., which may correspond to, for example, PSTN/ISDN nodes 330 of the embodiment(s) of FIGS. 3 et seq.) include both switching intelligence (e.g., which may correspond to, for example, one or more  
5 of processor(s) 332, switch and resource control software 333, signaling terminals 337, and STM/GPN translation table 339 of the embodiment(s) of FIGS. 3 et seq.) and switching fabric (e.g., which may correspond to, for example, an STM circuit switch 335 of the embodiment(s) of  
10 FIGS. 3 et seq.). While the nodes 410A,410B include connection control functions, they rely on the call control functions of the nodes 405A,405B to which they are respectively connected. In effect, each of the nodes 410A,410B (e.g., which may correspond to, for example, ATM  
15 nodes 340 of the embodiment(s) of FIGS.. 3 et seq.) include switching fabric (e.g., which may correspond to, for example, an ATM cell switch 345 of the embodiment(s) of FIGS. 3 et seq.). The nodes 410A,410B, which are also

connected to an ATM network 215, effect required emulation and cell packing for interworking a narrowband network (not shown) with the ATM network 215.

Generally, and in certain embodiment(s), call control  
5 involves features, functions, responsibilities, etc.  
pertaining to one or more of the following: routing a  
call; signaling between narrowband nodes; providing  
subscriber services; implementing charging; determining  
the connection and/or activation of tone senders,  
10 answering machines (e.g., voice mail), echo cancelers, and  
other types of telephony resources and/or equipment;  
ascertaining the desirability and/or necessity of  
utilizing an IN service; etc. Connection control, on the  
other hand, involves features, functions,  
15 responsibilities, etc. pertaining to setting  
up/establishing a connection between two (or among/across  
multiple) physical points within a switch and/or over a  
network responsive to call control, for example. The

connection control, to effectuate such a connection, may rely on some type of signaling of the bearer network (e.g., UNI, PNNI, B-ISUP, etc.)

In accordance with certain embodiment(s) of the present invention, the nodes 405A,405B may be advantageously realized using, at least partly, a modified version of an existing/legacy telecommunications switch. Using an existing telecommunications switch advantageously obviates any need to create code "from scratch" for the myriad of advanced calling features that are already supported by the existing telecommunications switch. Furthermore, in accordance with certain principles of the present invention, using an existing telecommunications switch enables a gradual migration to a broadband transport mechanism such as ATM. A call/connection control node 405A,405B and a respective connection control node 410A,410B pair together form a hybrid switch 420A/420B.

Referring now to FIG. 5, yet another exemplary scheme for utilizing a broadband network in conjunction with nodes having partially separated functions in accordance with the present invention is illustrated generally at 500. The two hybrid switches 420A, 420B are illustrated as being connected to the ATM network 215 by ATM links 505 (e.g., which may correspond to, for example, one or more of interface 300c, interface 300e, and ATM physical link 341 of the embodiment(s) of FIGS. 3 et seq.), e.g., via a connection control node 410. Each of the call/connection control node 405A and the connection control node 410A are connected to a Time Division Multiplexed (TDM) network 515 by TDM links 510 (e.g., which may correspond to, for example, interface 300d of embodiment(s) of FIGS. 3 et seq. [including alternative embodiment(s) of FIGS. 3 et seq. as described hereinabove with reference to the interface 300d of FIG. 3]; as well as interface 300b/link 351, interfaces 300b, 300c, and/or interface 300d/switch-

to-switch link 360). The TDM network 515 may correspond to any of many so-called narrowband networks such as PSTN, PLMN, ISDN, etc. As indicated within the hybrid switch 420A, the call/connection control node 405A is connected  
5 to the connection control node 410A via a TDM link 510 (e.g., which may correspond to, for example, interface 300b, interface 300c, interface 300d, switch-to-switch link 360, etc. of FIGS. 3 et seq.) and an ethernet link 520 (e.g., which may correspond to, for example, interface  
10 300a, interface 300b, interface 300c, switch-to-switch link 360, etc. of FIGS. 3 et seq.).

The hybrid switch 420 advantageously enables an existing switch in conjunction with an associated switch to facilitate the transport of call connections at least  
15 partly across a broadband network, such as the ATM network 215. As illustrated in the scheme 500, the existing switch may be realized using, for example, an AXE switch (available from Ericsson Inc.), and the associated switch

may be realized using, for example, an AXD 301 switch  
(also available from Ericsson Inc.). Thus, the hybrid  
switches 420A, 420B may be realized using, for example, an  
Ericsson Hybrid Switch (also available from Ericsson  
5 Inc.).

Referring now to FIG. 6, another exemplary hybrid  
switch with multiple ports for switching a connection in  
accordance with the present invention is illustrated  
generally at 420. The hybrid switch 420 includes a  
10 call/connection control node 405 and a connection control  
node 410 that are connected by linkage 605 (e.g., which  
may correspond to, for example, one or more of interface  
300a, interface 300b, interface 300c, interface 300d, and  
switch-to-switch link 360 of the embodiment(s) of FIGS. 3  
15 et seq.). It should be noted that the thick line  
representing the linkage 605 indicates that the linkage  
605 may be composed of more than one link. Information  
exchange across linkage 605 permits the call/connection

control node 405 to switch narrowband calls across the switching fabric of the connection control node 410. Such information exchange enables 64kbit/sec, narrowband calls originating and terminating in narrowband networks (e.g.,  
5 one or more TDM networks 515) to be trunked over broadband networks (e.g., one or more ATM networks 215) between hybrid switches 420. It should be noted that TDM as used herein, including the claims, encompasses and embraces time-division multiplexed protocols in general, and it is  
10 not limited to any particular TDM protocol.

The call/connection control node 405 includes input/outputs (I/Os) for two TDM links 510. Each TDM link 510 terminates at exchange termination (ET) equipment 610. Each ET equipment 610 is connected to a group switch (GS)  
15 615 (e.g., which may correspond to, for example, the STM circuit switch 335 of the embodiment(s) of FIGS. 3 et seq.). Each ET equipment 610 receives from the GS 615 data samples taken from multiple calls and multiplexes

this data into a stream of data sent out over a TDM link 510 that connects the hybrid switch 420 to another node. The ET equipment 610 also receives data from other nodes over the TDM link 510 and de-multiplexes this data into  
5 samples from separate calls to be transferred to the GS 615. The GS 615 is also connected to one or more signaling terminals (STs) 620 (e.g., which may correspond to, for example, the signaling terminals 337 of the embodiment(s) of FIGS. 3 et seq.). The linkage 605 may  
10 include a TDM link 510 (not explicitly shown in FIG. 6) that connects an ET equipment 610 of the call/connection control node 405 with a circuit emulation-ET (CE-ET) equipment 625 (e.g., which may correspond to, for example, the circuit emulation/translator 370 of the embodiment(s)  
15 of FIGS. 3 et seq.) of the connection control node 410.

The connection control node 410 includes I/Os for two TDM links 510. Each TDM link 510 terminates at CE-ET equipment 625 (e.g., which may correspond to, for example,



the extension terminal ET 346<sub>2</sub> (optionally in conjunction with the circuit emulation/translator 350) of the embodiment(s) of FIGS. 3 et seq.). Each CE-ET equipment 625 is connected to an ATM switch 630 (e.g., which may correspond to, for example, the ATM switch 345 of the embodiment(s) of FIGS. 3 et seq.). The CE-ET equipment 625 terminates a TDM link 510 for the ATM switching fabric of the connection control node 410 by using circuit emulation. The circuit emulation, e.g., hardware on a CE-ET equipment 625 maps time slots from an E1 line into, for example, single streams of ATM adaptation layer 1 (AAL1) cells. The CE-ET equipment 625 maps successive octets from a single time slot to a single stream of AAL1 cells. The ATM switch 630 is also connected to one or more ATM-ET equipments 635 (e.g., which may correspond to, for example, the extension terminal ET 346<sub>1</sub> of the embodiment(s) of FIGS. 3 et seq.). Each ATM-ET equipment

635 terminates an ATM link 505 to the ATM switching fabric of the connection control node 410.

The various ports/interfaces of the call/connection control node 405 and the connection control node 410 enable the establishment of various connection paths in the hybrid switch 420. Connection paths may be established across the following exemplary points as enumerated in Table 1:

10

15

20

(1) point A - (I, J) - G
(2) point A - (I, J) - H
(3) point D - (J, I) - B
(4) point E - (J, I) - B
(5) point C - (I, J) - G
(6) point C - (I, J) - H
(7) point D - (J, I) - F
(8) point D - G
(9) point D - H
(10) point E - (J, I) - F
(11) point E - G
(12) point E - H

Table 1 -- Connection Paths Establishable for FIG. 6.

Taking connection path "(6) point C - (I, J) - H", for example, a connection may be established from point "C" at the TDM link 510, through two ET equipments 610 and the GS 615, to point "I". The connection continues from point "I" across the linkage 605 to point "J". The connection continues further from point "J" through a CE-ET equipment 625, the ATM switch 630, and the ATM-ET equipment 635 to point "H" at the ATM link 505.

Referring now to FIG. 7, a simplified block diagram of an exemplary hybrid switch in accordance with the present invention is illustrated generally at 700. The hybrid switch at 700 includes a call/connection control node 405, which is shown connected to a TDM network 515 via a TDM link 510, and a connection control node 410, which is shown connected to a TDM network 515 via a TDM link 510 and an ATM network 215 via an ATM link 505. The call/connection control node 405 is connected to the

connection control node 410 via the linkage 605, which may include one or more links. The connection control node 410 includes connection control logic 705 and the ATM switch 630. The connection control logic 705 may be  
5 composed of, for example, hardware, software, firmware, some combination thereof, etc.

The ATM switch 630 is connected via link 710 to the GS 615 of the call/connection control node 405. The link 710 may be utilized to transfer data information between  
10 the ATM switch 630 and the GS 615. The call/connection control node 405 also includes connection control logic 715 to enable the call/connection control node 405 to switch calls (e.g., to or through the TDM network 515 directly connected thereto via the TDM link 510) without  
15 the aid of the connection control node 410. The connection control logic 715 may also be composed of, for example, hardware, software, firmware, some combination thereof, etc. The call/connection control node 405

further includes call control logic 720, which provides call control functions for the connection control node 410 as well as the call/connection control node 405. The call control logic 720 may also be composed of, for example,  
5 hardware, software, firmware, some combination thereof, etc.

The call control logic 720 may provide call control functions to the connection control node 410 by exchanging signaling information over a link 725. (It should be  
10 noted that either or both of the links 710 and 725 may be composed of more than one link.) For example, for a call incoming to the connection control node 410 over the TDM link 510 from the TDM network 515, signaling information may be forwarded to the call control logic 720 from the  
15 connection control logic 705 over the link 725. The switching intelligence of the call control logic 720 executes applicable call control functions and ascertains relevant call control information (e.g., as explained

further hereinabove with reference to FIGS. 3 et seq.).  
This signaling information is sent from the call control  
logic 720 over the link 725 to the connection control  
logic 705, which may thereafter switch the call data  
5 information of the incoming call to/through the  
appropriate network (e.g., the ATM network 215). The call  
control functions of existing (e.g., STM) switches can  
therefore be advantageously utilized by newer and faster  
(e.g., ATM) switches to thereby avoid needing to  
10 completely reprogram call control functionality for the  
newer switches.

It should be emphasized that the call/connection  
control node 405 is capable of connecting directly to the  
TDM network 515 over the TDM link 510 via the GS 615.  
15 Consequently, a hybrid switch architecture in accordance  
with the present invention, by combining a call/connection  
control node 405 with a connection control node 410,  
enables this logical node to communicate (i) with an

existing TDM network 515 (e.g., a PSTN network) using the  
GS 615 (e.g., an STM switch) and (ii) with a broadband  
network (e.g., the ATM network 215) over a broadband link  
(e.g., the ATM link 505) using a broadband switch (e.g.,  
5 the ATM switch 630). Providing such dual connectivity  
advantageously enables a network to gradually migrate from  
a first network protocol (e.g., a narrowband network  
protocol) to a second network protocol (e.g., a broadband  
network protocol) while utilizing both existing call  
10 control logic (e.g., software, etc.) and existing  
connections to and within the first network (e.g., a  
narrowband network).

Referring now to FIG. 8, exemplary communications and  
connections between nodes in another simplified block  
15 diagram of an exemplary hybrid switch in accordance with  
the present invention are illustrated generally at 800.  
In the exemplary hybrid switch 420, the call/connection  
control node 405 is connected to the connection control

node 410 via the linkage 605 at points I and J. The linkage 605 may be composed of multiple links. In this exemplary embodiment 800, a signaling information link 805 (e.g., which may correspond to, for example, interface 300a, interface 300b, interface 300c, switch-to-switch link 360, etc. of FIGS. 3 et seq.) and a data information link 810 (e.g., which may correspond to, for example, interface 300b, interface 300c, interface 300d, switch-to-switch link 360, etc. of FIGS. 3 et seq.) are illustrated as connecting the call/connection control node 405 to the connection control node 410. The signaling information link 805 may carry signaling communications between the call/connection control node 405 and the connection control node 410, and the data information link 810 may carry data communications between the call/connection control node 405 and the connection control node 410. Such data communications may include voice or data calls, for example.



In an exemplary embodiment, the signaling information link 805 is realized using two ethernet links. One ethernet link may be used for transmitting signaling information from the call/connection control node 405 to the connection control node 410 while the other ethernet link may be used for transmitting signaling information from the connection control node 410 to the call/connection control node 405. It should be understood that ethernet links are typically duplex in nature and that any ethernet links employed in any particular embodiment(s) in accordance with the present invention may also be duplex. The data information link 810 may be realized using a TDM link. For example, the data information link 810 may be composed of one or more E1 lines. Communications necessary and/or beneficial to establishing the various connections described hereinabove with reference to FIGS. 6 and 7, for example, may be effectuated across the signaling information link 805 and

the data information link 810. Advantageously, because separate links are employed between the nodes 405 and 410, signaling information and data information may be transferred therebetween across links 805 and 810, respectively, without needing to specify whether the transmitted information pertains to signaling or to data.

As illustrated generally at 800, the call/connection control node 405 is connected to two TDM networks 515, and the connection control node 410 is connected to two TDM networks 515 as well as two ATM networks 215. It should be noted that the number of networks to which the nodes 405 and 410 are connected is exemplary only. The flexibility of the hybrid node 420 advantageously enables calls to be incoming at either of the nodes 405 and 410 and to be forwarded via a connection of either of the nodes 405 and 410. In other words, a narrowband call incoming to the connection control node 410 (at point D)

or a broadband call (e.g., a narrowband call being carried by a broadband transport mechanism, etc.) incoming to the connection control node 410 (at point E) may be forwarded from the connection control node 410 (as a narrowband or  
5 broadband call at point G or point H, respectively) or from the call/connection control node 405 as a narrowband call (e.g., at point F). Furthermore, a narrowband call incoming to the call/connection control node 405 (at point C) may be forwarded from the call/connection control node  
10 405 as a narrowband call (at point F) or from the connection control node 410 (e.g., as a narrowband or broadband call at point G or point H, respectively). It should be noted that other combinations of ingress and egress (e.g., other connection paths) are possible.

15 By way of a first example but not limitation, assume that a call (or, more generally, a communication) is incoming to the connection control node 410 from a TDM network 515 at point D. The signaling information related

to the call (e.g., an ISUP Initial Address Message (IAM))  
is encapsulated into ATM cells (e.g., at the CE-ET  
equipment 625 at point D) and passed to the ATM switch  
630. Advantageously, the signaling information may  
5 therefore be piped through the connection control node 410  
and over the signaling information link 805 without  
reformatting after being de-packaged from ATM cells (e.g.,  
at the CE-ET equipment 625 at point J). The signaling  
information therefore need not be modified inasmuch as it  
10 may be transported through "transparent" pipes across the  
ATM switching fabric of the connection control node 410  
(e.g., using a permanent virtual path connection (PVPC)  
pipe or similar, etc.).

When the GS 615 and associated call control logic  
15 (not explicitly shown in FIG. 8) receive the signaling  
information of the incoming call, the signaling  
information is analyzed (e.g., by an ST 620 at point A or  
point B). The traffic call handling is performed by, for

example, performing a B-number analysis, accessing an interactive voice response system, contacting an Intelligence Network (IN) node 815 (e.g., for "(800)" call routing, etc.), consulting a database of bearer  
5 capabilities for destination and/or transit nodes, etc. If, in contradistinction to the example described hereinabove with reference to FIG. 3A, the call/connection control node 405 determines that the call should not or can not be routed through a broadband ATM transport  
10 mechanism, then the call/connection control node 405 instructs the connection control node 410 (e.g., over the signaling information link 805) to route the data information of the call to (and through) the call/connection control node 405.

15       The data information of the call is routed through the connection control node 410 from point D to point J (e.g., by piping the data information via a semi-permanent connection through the switching fabric of the ATM switch

630). It should be noted that the data information may be propagated through the connection control node 410 without reformatting by, for example, encapsulating the data information in ATM cells. Thereafter, the data  
5 information is forwarded from point J to point I over the data information link 810 in, for example, a TDM format. The ET equipment 610 receives the data information of the call, and the GS 615 switches it toward the appropriate TDM network 515 (e.g., through an ET equipment 610 to a  
10 point C or a point F) in accordance with the earlier traffic call analysis.

By way of a second example but not limitation, assume that a call is incoming to the call/connection control node 405 from a TDM network 515 at point C. The  
15 call/connection control node 405 performs a traffic call analysis based on signaling information of the call. If the analysis indicates that the call can (and optionally should) be sent over a broadband transport mechanism, the

call/connection control node 405 can direct the incoming call through the connection control node 410 and then to an ATM network 215, instead of directing the call to a TDM node in a TDM network 515 (e.g., through the ET equipment 610 at the point F). In this regard, the GS 615 may switch the call signaling information to the ATM switch 630 via the signaling information link 805 and the call data information to the ATM switch 630 via the data information link 810 (and appropriate ET equipment 610 and CE-ET equipment 625 at point I and point J, respectively). The ATM switch 630 may thereafter send the signaling information of the call over permanent connections set up in the broadband ATM network 215 and the data information of the call over, e.g., call-specific connections in the broadband ATM network 215 (via an ATM-ET equipment 635 at point E or point H).

Referring now to FIG. 9, an exemplary method in flowchart form for communicating between nodes in a hybrid

switch in accordance with the present invention is illustrated generally at 900. In the exemplary method of flowchart 900, an incoming call is initially received at a first node (step 905). The first node sends signaling  
5 information related to the incoming call to a second node via a first link (step 910). The second node, which may provide call control for the first node, processes the signaling information (step 915) to determine how and to where the incoming call is to be routed. The second node  
10 sends instructions to the first node (e.g., via the first link) (step 920) directing the first node on how/where to route the incoming call. Assuming that the second node determined that the incoming call should be routed as an outgoing call from the second node (at step 915) and that  
15 the instructions sent to the first node (at step 920) so indicated, data information related to the incoming call is sent from the first node to the second node via a second link (step 925).



Alternatively, an incoming call can be received at a node capable of processing the corresponding signaling information. Accordingly, both signaling information and data information corresponding to the incoming call may be  
5 sent to an associated node via first and second links, respectively, if the node receiving the incoming call determines that it is appropriate to do so (e.g., as described hereinabove in the second example referencing FIG. 8). The call control functions of existing (e.g.,  
10 STM) switches can therefore be advantageously utilized by newer and faster (e.g., ATM) switches to thereby avoid needing to completely reprogram the call control functionality for the newer switches. Furthermore, hybrid switches including both narrowband and broadband switches  
15 enable greater versatility for switching communications between broadband and narrowband transport mechanisms. For example, a hybrid switch may receive a communication that is being transported in a narrowband format and

forward the communication in a broadband format, or vice versa. This ability is particularly advantageous for enabling a gradual migration in a network from being primarily or entirely narrowband to being primarily or  
5 entirely broadband.

Referring now to FIGS. 10A-10E, a first set of exemplary traffic scenarios for a hybrid switch in accordance with the present invention is illustrated. In FIG. 10A, a hybrid switch 420 is illustrated as being  
10 connected to two local exchange/transit exchange (LE/TE) nodes via TDM links, which may operate using an "N-ISUP" protocol, for example. The hybrid switch 420 is illustrated as receiving and forwarding a communication 1000. It should be understood that the detailed traffic  
15 scenarios illustrated in FIGS. 10B-10E are also applicable to other instances besides when a hybrid switch 420 is directly connected to a local exchange/transit exchange node on both sides of a communication 1000. For instance,

the traffic scenarios of FIGS. 10B-10E are applicable whenever both the incoming and the outgoing side of a communication are transported on a narrowband transport mechanism such as TDM.

5           In FIG. 10B, the communication 1010 (which represents a particular traffic scenario and/or portion of the communication 1000) may be terminated and switched entirely within the narrowband portion of the hybrid switch 420. In FIG. 10C, the incoming side of a  
10       communication 1020 is terminated in the narrowband portion of the hybrid switch 420 while the outgoing side is terminated at the broadband portion (e.g., using a circuit emulation (CE) board). The switching occurs partly within the narrowband portion and partly within the broadband  
15       portion of the hybrid switch. In FIG. 10D, both of the incoming and the outgoing sides of a communication 1030 are terminated in the broadband portion of the hybrid switch 420. In this scenario, a, e.g., circuit emulation

board is utilized on both the ingress and the egress sides of the, e.g., TDM connection. The switching may be effectuated entirely within the switching fabric of the broadband portion. In FIG. 10E, the incoming side of a communication 1040 is terminated by the broadband portion of the hybrid switch 420 whereas the outgoing side is terminated at the narrowband portion. Switching of the communication 1040 is therefore effectuated partly within the broadband portion (e.g., using an ATM switch 630) and partly within the narrowband portion (e.g., using a GS 615) of the hybrid switch 420.

Referring now to FIGS. 10F-10K, a second set of exemplary traffic scenarios for a hybrid switch in accordance with the present invention is illustrated. In FIG. 10F, multiple hybrid switches 420 are illustrated as being connected to each other and ultimately to two local exchange/transit exchange nodes. The hybrid switches 420 are illustrated as receiving and forwarding a

communication 1000. A connection between two hybrid switches 420 may be realized using an ATM link, which may carry an "N-ISUP" protocol thereon, for example. A connection between a hybrid switch 420 and a local exchange/transit exchange may be realized using a TDM link, which may operate using an "N-ISUP" protocol, for example.

It should be understood that the detailed traffic scenarios illustrated in FIGS. 10G-10J are also applicable to other instances besides when a hybrid switch 420 is directly connected to a local exchange/transit exchange node on a single side of a communication 1000. For instance, the traffic scenarios of FIGS. 10G-10J are applicable whenever one side of a communication is transported on a narrowband transport mechanism such as TDM and the other side of the communication is transported on a broadband transport mechanism such as ATM. Likewise, it should be understood that the detailed traffic scenario

illustrated in FIG. 10K is also applicable to other instances besides when a hybrid switch 420 is directly connected to hybrid switches 420 on both sides of a communication 1000. For instance, the traffic scenario of  
5 FIG. 10K is applicable whenever both sides of a communication are transported on a broadband transport mechanism such as ATM.

In FIG. 10G, a communication 1050 is terminated at the incoming (e.g., TDM) side by the narrowband portion of  
10 the hybrid switch 420. The switching of the communication 1050 may be performed by both the narrowband and the broadband portions after accommodation of the differing formats (e.g., by a circuit emulation board). The termination of the outgoing (e.g., ATM) side of the  
15 communication 1050 is effectuated (e.g., by an exchange termination (ET) board) at the broadband portion of the hybrid switch 420. In FIG. 10H, the incoming side of a communication 1060 is terminated (e.g., by a circuit

emulation board for a narrowband transport format) at the  
broadband portion of the hybrid switch 420. Switching of  
the communication 1060 may be performed entirely within  
the switching fabric of the broadband portion of the  
5 hybrid switch, and termination (e.g., by an exchange  
termination board for a broadband transport format) of the  
outgoing side of the communication 1060 may be  
accomplished by the broadband portion as well.

In FIG. 10I, the incoming side of a communication  
10 1070 is terminated (e.g., by an exchange termination board  
for a broadband transport format) at the broadband portion  
of the hybrid switch 420. Switching of the communication  
1070 may be performed entirely within the switching fabric  
of the broadband portion of the hybrid switch 420, and  
15 termination (e.g., by a circuit emulation board for a  
narrowband transport format) of the outgoing side of the  
communication 1070 may be accomplished by the broadband  
portion as well. In FIG. 10J, a communication 1080 is

terminated at the incoming (e.g., ATM) side by the broadband portion of the hybrid switch 420 (e.g., using an exchange termination board). The switching of the communication 1080 may be performed by both the narrowband  
5 and the broadband portions after accommodation of the differing formats (e.g., by a circuit emulation board). The termination of the outgoing (e.g., TDM) side of the communication 1080 is effectuated at the narrowband portion of the hybrid switch 420.

10 In FIG. 10K, the hybrid switch may act as a "pure transit node" for ATM connections, such as the illustrated portion of the communication 1000, which is denoted as a communication 1090. Both of the incoming and the outgoing sides of the communication 1090 are terminated by the  
15 broadband portion of the hybrid switch 420 (e.g., by two exchange termination boards). Also, the communication 1090 may be switched entirely by the switching fabric (e.g., as realized by an ATM switch 630) of the broadband



portion of the hybrid switch 420. As also described and  
alluded to with reference to, for example, FIG. 6  
hereinabove, a hybrid switch 420 may establish various  
connection paths within to thereby enable a myriad of  
5 combinations of external ingress points and external  
egress points for different types of communications. The  
hybrid switch 420 may thus receive and forward  
communications 1000 in any combination of incoming and  
outgoing narrowband and broadband formats to accommodate,  
10 for example, the next node along the communication path,  
a node that is proximal to the final destination of the  
communication 1000, etc.

Referring now to FIG. 11, an exemplary outgoing  
communication format selection for a hybrid switch in  
15 accordance with the present invention is illustrated  
generally at 1100. An incoming communication 1105 is  
illustrated as being either broadband (e.g., ATM  
formatted) or narrowband (e.g., TDM formatted). The

hybrid switch 420, as described hereinabove with reference to FIGS. 10A-10K, for example, may forward the communication 1105 as either an ATM communication or a TDM communication. (It should be understood that an outgoing  
5 TDM communication may be terminated by either the narrowband portion or the broadband portion of the hybrid switch 420. However, this detail is not directly addressed further in the context of FIG. 11.) The hybrid switch 420 may forward the communication on the outgoing  
10 side according to any of various algorithms. For example, the hybrid switch may forward all incoming communications 1105 as outgoing TDM communications 1115 (e.g., if the hybrid switch 420 is the first or one of the first hybrid switches to be installed in a traditionally narrowband  
15 network) or as outgoing ATM communications 1120 (e.g., if the hybrid switch 420 is the last or one of the last hybrid switches to be installed in a formally narrowband

network). Refer also to the text hereinabove describing  
FIG. 3H.

Alternatively, the hybrid switch 420 may consult a  
table 1110 that provides an indication as to the viability  
5 and/or desirability of forwarding the communication 1105  
in either a broadband or a narrowband format. For  
example, the table 1110 may indicate whether a node  
associated with the destination terminal 1155 or 1170 is  
capable of broadband transport. The table 1110 may also  
10 or in the alternative indicate whether any nodes between  
the hybrid switch 420 and the destination terminal 1155  
and 1170 are capable of broadband transport. An exemplary  
embodiment for table 1110 is discussed hereinabove with  
reference to, for example, FIG. 3A, Events E8 and E9, and  
15 may involve the ascertainment of the bearer type (of  
either or both of the incoming side of the communication  
and the destination terminal). It should be noted that  
the table 1110 may be realized, instead of being part of

the narrowband portion of the hybrid switch 420 but  
separate from the GS as illustrated, as part of the GS  
(e.g., the GS 615), as any part of the broadband portion  
(e.g., the ATM switch 630), as another part of the hybrid  
5 switch 420, or even at an external location (e.g., an IN  
node), etc.

Alternatively, instead of relying on information in  
a table 1110, the hybrid switch may query a node at or  
proximate to the destination node, may send a test  
10 signal/communication, etc. Regardless, if the hybrid  
switch 420 determines that there is a broadband node  
associated with the destination terminal, the hybrid  
switch 420 may elect to forward the incoming communication  
1105 as a broadband (e.g., ATM) communication 1120. The  
15 hybrid switch 420' receives the incoming broadband  
communication 1120 and forwards an outgoing narrowband  
(e.g., TDM) communication 1160 to a local exchange node  
1165 (e.g., which may correspond to, for example, an

access node 322, etc. of FIGS. 3 et seq.), which connects to the destination terminal 1170 (e.g., which may correspond to, for example, a terminal 324, etc. of FIGS. 3 et seq.).

5           If, on the other hand, the hybrid switch 420 determines that there is not a broadband node associated with the destination terminal, the hybrid switch 420 may elect to forward the incoming communication 1105 as a narrowband (e.g., TDM) communication 1115. However, the  
10       hybrid switch 420 may optionally include provisions for determining that one or more (e.g., a sufficiently high enough number of intervening nodes have broadband capability, a sufficiently shorter route may be defined across intervening broadband-enabled network nodes, etc.)  
15       intervening broadband nodes may be advantageously utilized along the overall communication path. If such a determination is made, the hybrid switch 420 may elect to forward the incoming communication 1105 as a broadband

(e.g., ATM) communication 1125 through a broadband-enabled network portion 1130. Regardless, the communication is or ultimately becomes/is converted to a narrowband (e.g., TDM) communication and is submitted as narrowband communication 1135 to the narrowband node 1140. The narrowband node 1140 forwards the incoming narrowband communication 1135 as an outgoing narrowband (e.g., TDM) communication 1145 to a local exchange 1150 (e.g., which may correspond to, for example, an access node 322, etc. of FIGS. 3 et seq.), which connects to the destination terminal 1155 (e.g., which may correspond to, for example, a terminal 324, etc. of FIGS. 3 et seq.).

Referring now to FIG. 12, exemplary interactions between a hybrid switch and other telecommunications technology in accordance with the present invention are illustrated generally at 1200. The hybrid switch 420 of 1200 illustrates the traffic scenarios or communication portions 1010-1090 of communication 1000 (of FIGS. 10A-

10K). Communication 1205 (illustrated generally as a line or loop) enables a communication 1010-1090 according to any of the various traffic scenarios to access telecommunications technology using TDM communication and  
5 a STM switch (e.g., a GS 615). For example, one or more IN nodes 815 of an IN (not explicitly shown in FIG. 12) may be accessed via the communication 1205. Many telecommunications services and features may be utilized by accessing the IN. A DTMF receiver 1210, for example,  
10 may be accessed for password and account number reception and for sending announcements from the IN. Generally, specialized resource function (SRF) and service control function (SCF) features are accessible via the IN node 815. These and other IN features are represented  
15 generally by the other block 1215. Access to the IN node 815 may be accomplished during the call establishment phase. Thereafter, routing of the communication 1000 may optionally be maintained through the narrowband portion of

the hybrid switch 420. Regardless, the communication 1000 may be routed through the narrowband portion (e.g., the GS 615) during an active call phase in order to access IN features.

5           The communication 1205 may also enable access to the operator 1220 for the communication 1000 (of FIGS. 10A-10K). The operator 1220 may handle the telecommunications situation and thereafter route the connection further along communication 1205 to implement one of the  
10           illustrated traffic scenarios. Alternatively (e.g., depending on how the operator 1220 handles the telecommunications situation), the operator 1220 may independently forward the connection towards, e.g., another exchange as indicated by arrow 1225. The  
15           communication 1205 may also enable access to legal intercept (LI) equipment 1230. It should be noted that with respect to FIG. 12, as well as other FIGS. described herein, certain elements may be moved, changed in number,



etc. without departing from the scope of the present invention. For example, with regard to the hybrid switch 420 of FIG. 12, only two ET equipments may be associated with the GS (instead of the four illustrated), and the CE  
5 equipment between the GS and the ATM switch may be more closely associated with the ATM switch than the GS (e.g., as illustrated in FIG. 11).

The hybrid nature of the hybrid switch 420, in addition to enabling a gradual migration from a  
10 narrowband-oriented network to a broadband-oriented network, also enables seamless integration with networks of other carriers, networks of mobile systems, and networks that are international (all of which are designated generally by the external networks 1240). The  
15 external networks 1240 currently operate in accordance with TDM principles (or at least they are designed to interface with other networks using TDM principles), and they may continue to do so for quite some time into the

future. The hybrid switch 420, while providing the ability to transport communications on a broadband transport mechanism, also maintains the ability to utilize a narrowband transport mechanism and the ability to interface with external networks 1240 using traditional protocols. For example, communication 1205 enables outgoing connections (as represented by arrow 1235) and incoming connections (as represented by arrow 1245) between the hybrid switch 420 and the external networks 1240.

Referring now to FIG. 13, an exemplary traffic scenario migration for a hybrid switch in accordance with the present invention is illustrated generally at 1300. The hybrid switch 420 may be "installed" in an existing network that utilizes, at least primarily, a narrowband transport mechanism. The hybrid switch 420 may be "installed", for example, by augmenting an existing TDM switch with ATM switching fabric. When the hybrid switch

420 is initially installed, especially if it is one of the first such switches installed, the hybrid switch may be activated or set up to operate entirely or predominantly within a first exemplary mode. Such a first exemplary mode may entail receiving a communication 1305 (e.g., as incoming TDM) and forwarding the communication 1305 (e.g., as outgoing TDM) using the switching fabric (e.g., a GS 615) of the existing narrowband switch. Gradually, as additional broadband-enabled nodes are "brought on-line", the hybrid switch 420 may enter a second exemplary mode. Such a second exemplary mode may entail receiving a communication 1310 (e.g., as incoming TDM) and forwarding the communication 1310 (e.g., as outgoing ATM) using the switching fabric of the existing narrowband switch as well as the switching fabric (e.g., an ATM switch 630) of the broadband switch.

As the hybrid switch 420 of 1300 begins to receive incoming communications that use a broadband transport

mechanism such as ATM, the hybrid switch 420 may enter a third exemplary mode. Such a third exemplary mode may entail receiving a communication 1315 (e.g., as incoming ATM) and forwarding the communication 1315 through the switching fabric of the broadband switch and the switching fabric of the narrowband switch to be handled by narrowband telecommunications technology and/or telecommunications technology with narrowband interface(s). For example, the communication 1315 may be forwarded from the narrowband switch as communication 1315' to a voice response unit 1320 to provide voice response service to the communication 1315 that originally arrived at the hybrid switch 420 using a broadband transport mechanism. Alternatively, the communication 1315 may be forwarded from the narrowband switch as communication 1315'' (as indicated by the arrow so labeled) to external network(s) 1240. If the communication 1315 is to continue within the network of

the hybrid switch 420 (or otherwise forwarded as a  
broadband connection therefrom), the communication 1315'  
is returned to the narrowband switching fabric (e.g.,  
after being serviced by the voice response unit 1320 or  
5 other such existing narrowband features) and forwarded to  
and through the broadband switching fabric as the  
communication 1315' (e.g., as outgoing ATM).

Eventually, as the network becomes wholly or  
primarily a broadband transport mechanism network  
10 (optionally including broadband provision of IN-type  
services, etc.), the hybrid switch 420 of 1300 may enter  
a fourth exemplary mode. Such a fourth exemplary mode may  
entail receiving a communication 1325 (e.g., as incoming  
ATM) and forwarding the communication 1325 (e.g., as  
15 outgoing ATM) using the switching fabric of the broadband  
portion of the hybrid switch 420. It should be understood  
that the four modes illustrated and described herein with  
reference to FIG. 13 are exemplary only. Modes may be

added, subtracted, or substituted for the four exemplary modes depending, for example, on the percentage of the network that has been upgraded to broadband. Furthermore, the modes may be activated in a different order depending, 5 for example, on whether or not the hybrid switch in question is a "transit-type" node.

Referring now to FIG. 14, an exemplary method in flowchart form for enabling a gradual migration from a primarily narrowband network to a primarily broadband 10 network in accordance with the present invention is illustrated generally at 1400. Initially, a network node (e.g., a hybrid switch 420) receives an incoming communication that includes an identifier corresponding to a destination terminal (e.g., a destination terminal 1155 15 and 1170 (of FIG. 11)) (step 1405). The incoming communication may be transported, for example, on a broadband or narrowband mechanism. The identifier that corresponds to the destination terminal is analyzed (step

1410). The identifier may correspond to, for example, a B-number, and the identifier may be analyzed, for example, in a narrowband portion of the network node. The analysis may include a determination as to whether or not the  
5 identifier is associated with a node having broadband capability (step 1415). If not, then the communication may be forwarded over a narrowband transport mechanism (step 1420) and ultimately to the destination terminal.

If, on the other hand, it is determined that the  
10 identifier is associated with a node having broadband capability (at step 1415), then the communication may be forwarded over a broadband transport mechanism (step 1425) and ultimately to the destination terminal. The identifier may be associated with a node when, for  
15 example, the node is the most proximate node (or the most proximate non-local exchange and/or non-end office node) to the destination terminal. The identifier, in addition to or in the alternative, may be associated with a node

when the node is somewhere between the analyzing node and the destination terminal, but the node is sufficiently far from the analyzing node and sufficiently close to the destination terminal so as to warrant diverting (if  
5 necessary) the communication onto a broadband transport mechanism. The analysis may involve accessing a table (or other data structure) (e.g., a table 1110), which may be gradually updated as nodes in the network are upgraded to provide broadband transport. In an alternative  
10 embodiment, a communication may only be forwarded using a broadband transport mechanism (e.g., in step 1425) if a node having broadband capability is also associated with an identifier that corresponds to an originating terminal and/or if the incoming communication "arrives" over a  
15 broadband transport mechanism. In yet another alternative, the broadband capability of a node associated with the identifier that corresponds to the originating terminal may be another factor to account for when



analyzing the proximity of the node associated with the identifier of the destination terminal. A hybrid switch operated in accordance with certain principles of the present invention therefore enables a gradual migration  
5 from a narrowband-oriented network to a broadband transport mechanism-oriented network.

Referring now to FIG. 15, an exemplary tri-level nodal environment in accordance with the present invention is illustrated generally at 1500. A call/connection  
10 control node 405 (e.g., which may correspond to, for example, PSTN/ISDN nodes 330 of the embodiment(s) of FIGS. 3 et seq.) is illustrated connected to a modified connection control node 410' (e.g., which may correspond to, for example, ATM node 340<sub>7-1</sub> of the embodiment(s) of  
15 FIGS. 3 et seq.) via line 1510 (e.g., which may correspond to, for example, interface 300a and/or interface 300d of the embodiment(s) of FIGS. 3 et seq.). The modified connection control node 410', in the exemplary tri-level

nodal environment 1500, includes an interworking function (IWF) 1505 (e.g., which may correspond to, for example, an IWF 344<sub>7-1</sub> of the embodiment(s) of FIGS. 3 et seq.). The IWF 1505 may be composed of, for example, hardware, software, firmware, some combination thereof, etc.

The IWF 1505 may include emulation and mapping capabilities. For example, the IWF 1505 may include the ability to emulate a switch interface for the call/connection control node 405. Advantageously, this eliminates any absolute requirement to modify the call/connection control node 405 because the call/connection control node 405 is able to act and interact as if it is functioning within a traditional telecommunications network. The IWF 1505 may also include the ability to map/translate one network address into or to another network address. The modified connection control node 410' is illustrated connected to multiple connection control nodes 410 (e.g., which may correspond

to, for example, ATM node 340<sub>7-2</sub>, ATM node 340<sub>7-3</sub>, etc. of  
the embodiment(s) of FIGS. 3 et seq.) via lines 1515  
(e.g., which may correspond to, for example, interfaces  
300a and/or interfaces 398 of the embodiment(s) of FIGS.  
5 3 et seq.). In the exemplary tri-level nodal environment  
1500, the call/connection control node 405 may  
advantageously provide/share its switching intelligence  
with more than one connection control node 410. It should  
be understood that the various nodes may be physically co-  
located, physically separated, etc.  
10

Referring now to FIG. 15A, a first exemplary tri-  
level nodal environment alternative in accordance with the  
present invention is illustrated generally at 1525. In  
the first exemplary tri-level nodal environment  
15 alternative 1525, the call/connection control node 405 is  
in communication with the modified connection control node  
410' via a first line 1530 and a second line 1535. The  
first line 1530 and the second line 1535 may be used for

communicating signaling information and data information,  
respectively, between the call/connection control node 405  
and the modified connection control node 410', which has  
the IWF 1505. Also illustrated in the first exemplary  
5 tri-level nodal environment alternative 1525 is an ATM  
network 215 cloud interconnecting the modified connection  
control node 410' and the connection control nodes 410.  
In other words, the modified connection control node 410'  
need not employ direct and dedicated links to the  
10 individual connection control nodes 410. It should be  
understood that the ATM network 215 may alternatively be  
realized as any circuit-switched network.

Referring now to FIG. 15B, a second exemplary tri-  
level nodal environment alternative in accordance with the  
15 present invention is illustrated generally at 1550. In  
the second exemplary tri-level nodal environment  
alternative 1550, a "combined" tri-level nodal environment  
is illustrated. The modified call control node 405' does

not include connection control (e.g., it was designed and built without such connection control, it had its connection control removed or rendered inoperable, etc.), and no single connection control is directly associated  
5 with (or co-located with) the IWF (node) 1505. The switching intelligence of the modified call control node 405' operates in a first address space, which is designated address space A 1555. The switching fabric of the multiple connection control nodes 410, on the other  
10 hand, operate in a second address space, which is designated address space B 1560. The IWF 1505 maps/translate the addresses of the address space A 1555 to the addresses of the address space B 1560 so as to enable the switching intelligence of the modified call  
15 control node 405' to provide call control to the switching fabric of the multiple connection control nodes 410.

It should be understood that while the address spaces A 1555 and B 1560 are illustrated only in the second

exemplary tri-level nodal environment alternative 1550,  
they are also applicable to the exemplary tri-level nodal  
environment 1500 as well as the first exemplary tri-level  
nodal environment alternative 1525. It should also be  
5 understood that the different aspects illustrated in the  
various embodiments of FIGS. 15, 15A, and 15B may be  
interchanged without departing from the present invention.  
For example, a circuit-switched network cloud (e.g., the  
ATM network 215) may interconnect the multiple connection  
10 control nodes 410 in any or all embodiments embraced by  
the present invention.

Referring now to FIG. 15C, an exemplary interworking  
function in accordance with the present invention is  
illustrated at 1505. The IWF 1505 includes an emulator  
15 1580 and a mapper (or translator) 1585. The emulator 1580  
emulates an interface to which the call/connection control  
node 405 "expects" to be connected. In other words, the  
emulator 1580 may provide an interface that the

call/connection control node 405 is already designed to  
utilize and/or interact with. Advantageously, this  
eliminates or minimizes or at least reduces the need to  
modify the call/connection control node 405. It should be  
5 noted that the interface may be equivalent to a GS  
input/output (I/O), E1/T1 trunk lines, etc. The mapper  
1585 provides a mapping (or more generally a  
correspondence) between addresses of a first address space  
and addresses of a second address space.

10 The mapper may map (or more generally a  
correspondence may be established between) address space  
A 1555 (of FIG. 15B) to the address space B 1560. For  
example, one or more of the addresses A1... An of the  
address space A 1555 may be mapped to one or more of the  
15 addresses B1... Bn of the address space B 1560. As a  
specific instance, the address A3 may be mapped to the  
address B1. In exemplary embodiment(s), the address space  
A 1555 may include 10-digit B-numbers, and the address

space B 1560 may include ATM identifiers such as VPIs and VCIIs. Other exemplary address space realizations are also embraced by the present invention.

Referring now to FIG. 16, an exemplary tri-level  
5 nodal environment implementation in accordance with the present invention is illustrated generally at 1600. A telecommunications node (TN) 1605 (e.g., which may correspond to, for example, a call/connection control node 405 of the embodiment(s) of FIGS. 15 et seq.) is shown  
10 connected to media gateway functionality 1615 (e.g., which may correspond to, for example, a modified connection control node 410' of the embodiment(s) of FIGS. 15 et seq.). The TN (a.k.a. legacy switch (LS)) 1605 may have a circuit switch such as a GS 615 (not explicitly shown in  
15 FIG. 16). The media gateway functionality 1610 may include a media gateway (MG) 1615, which may have a packet switch such as an ATM switch 630, and mediation logic (ML)



1620 (e.g., which may correspond to, for example, an IWF  
1505 of the embodiment(s) of FIGS. 15 et seq.).

The media gateway functionality 1610 is illustrated  
as being connected to multiple MGs 1625 (e.g., which may  
5 correspond to, for example, the multiple connection  
control nodes 410 of the embodiment(s) of FIGS. 15 et  
seq.). Each of the MGs 1625 may be responsible for  
handling one or more different types of media. The media,  
and nodes corresponding thereto, may include, for example,  
10 a remote subscriber switch (RSS) node 1630A, a V5.2  
interface access network (V5.2) node 1630B, a local  
exchange (LE) node 1630C, a primary rate access (PRA) node  
1630D, etc. An MG 1625 (or an MG 1615) may convert media  
provided in one type of network to the format requirements  
15 of another type of network.

Exemplary and/or appropriate protocols for the links  
between the various illustrated nodes (including the  
gateways) are illustrated at the exemplary tri-level nodal

environment implementation 1600. As an explanatory example, the connections between the media gateway functionality 1610 and the multiple MGs 1625 may be ATM-ET to ATM-ET PVPC pipes defined through an ATM network to  
5 carry signaling information. A PVPC is an ATM connection in which the switching is performed only on the VPI field of each cell. A PVPC is termed "permanent" because it is provisioned through a network management function and maintained (or left up) indefinitely. The signaling  
10 information between the media gateway functionality 1610 and any one or more of the MGs 1625 may be effectuated transparently over a PVPC pipe. Such a PVPC pipe is at least similar to one establishable through the switching fabric of a connection control node 410 for transparently  
15 piping signaling information to the switching intelligence of a call/connection control node 405 (as alluded to hereinabove with reference to FIGS. 3 et seq.).

Referring now to FIGS. 17A and 17B, two other exemplary tri-level nodal environment implementations in accordance with the present invention are illustrated generally at 1700 and 1750, respectively. The exemplary  
5 tri-level nodal environment implementations 1700 and 1750 include call servers 1705. The call servers 1705 each include a TN 1605 and ML 1620. Each call server 1705 may control one or more MGs 1625 (denoted as "MGW" in FIGS. 17A and 17B) via the packet-switched network cloud, such  
10 as an ATM network 215. Each call server 1705, being based on pre-existing TNs 1605 in certain exemplary embodiment(s), may only handle a finite number of MGs 1625. Accordingly, a given tri-level nodal environment may need more than one call server 1705, as indicated by  
15 the two call servers 1705 illustrated in the exemplary tri-level nodal environment implementation 1750.

The bearer services for call data information are provided by the packet-switched broadband network (e.g.,

via encapsulation), and the telecommunications services/call control may be transported over this packet-switched (broadband) network in an un-modified format (e.g., transparently in pipes), as indicated by the dashed  
5 lines. For example, control communications to the private branch exchange (PBX) nodes 1710A are effectuated using DSS1, control communications to the generic access nodes (AN) 1710B are effectuated using V.5, and control communications to the LE nodes 1630C are effectuated using  
10 ISUP. Likewise or similarly, the two call servers 1705 may communicate therebetween using a bearer independent call control (BICC) protocol that may be transported over the packet-switched network. It should be emphasized that TDM as used herein, including the claims, encompasses and  
15 embraces time-division multiplexed protocols in general, and it is not limited to any particular TDM protocol, including the exemplary 2M PCM link definition of FIGS. 17A and 17B.

With reference now to FIGS. 18A and 18B, two exemplary call setups in an exemplary tri-level nodal environment implementation in accordance with the present invention are illustrated generally at 1800 and 1850, respectively. In the exemplary call setup 1800, a TN 1605 determines that a communication path between points A and B are needed for a call. The TN 1605 therefore instructs the ML 1620 to establish a path between the points A and B. The instruction may include direction(s) for establishing such a path in a TDM network. The ML 1620, applying the points A and B and/or the direction(s) to a mapping data structure for example, determines how to establish a communication path between points A and B. The ML 1620 then instructs/requires that such a communication path be established (e.g., added) in the broadband network of which the MG 1625 is a part. In the exemplary call setup 1800, an intra MG call setup case is

illustrated, so the single MG 1625 that is illustrated is capable of establishing the communication path.

In the exemplary call setup 1850, on the other hand, a multi-MG (but intra domain) call setup case is illustrated, so more than a single MG 1625 is required to establish the communication path. Specifically, after the ML 1620 receives the instruction (and possibly the direction(s)) from the TN 1605, the ML 1620 determines that the communication path needs to extend between at least two MGs 1625. Namely, the MGs 1625 that include the points A and B need to be interconnected, optionally with no intervening MG(s) 1625. In the exemplary call setup 1850, the ML 1620 then instructs/requires that such an interconnection for the communication path be established (e.g., added) in the broadband network between the MG 1625AC' and the MG 1625D'B, as indicated by the dashed line. The MGs 1625AC' and 1625D'B also complete the communication path between point A and point B by

establishing interconnections between points A and C' and points D' and B, respectively. By determining a communication path and/or instituting a routing of a communication path between point A and point B through a packet-switched (broadband) network, the ML 1620 effectively maps from one address space to another address space.

Referring now to FIG. 19, exemplary communication path configuring in an exemplary tri-level nodal network in accordance with the present invention is illustrated generally at 1900. The entities responsible for configuring various communication paths in the exemplary tri-level nodal network 1900 are indicated by the type of line (e.g., solid, dashed, thick, thin, etc.) illustrating/representing the particular communication path. The signaling link parts represented by the solid thick lines (also labeled "(A)") are configured by TN 1605 commands. The signaling link parts represented by the

solid thin lines (also labeled "(B)") are configured by ATM management system commands. The leased line parts represented by the dashed thick lines are configured by TN 1605 commands. The leased line parts represented by the  
5 dashed thin lines (also labeled "(C)" and "(D)") are configured by ATM management system commands. The parts labeled "(A)" and "(C)" pertain to intra-domain segments while the parts labeled "(B)" and "(D)" pertain to inter-domain segments. It should be noted that segments within  
10 the ATM network are configured by the ATM management system commands while segments extending beyond the ATM network are configured by TN 1605 commands in the exemplary communication path configuring of the exemplary tri-level nodal network 1900.

15 Referring now to FIGS. 20A and 20B, exemplary mapping embodiments in an exemplary tri-level nodal environment implementation in accordance with the present invention are illustrated generally at 2000 and 2050, respectively.



The exemplary mapping as illustrated at 2000 includes a man machine line (MML) handler 2005 and an ATM management system 2010 that enable the general management of the illustrated tri-level nodal environment implementation.

5 Specifically, the MML handler 2005 enables the configuring of the TN 1605 portion, and the ATM management system 2010 enables the configuring of the ML 1620 and MG 1625 portions. Switch device management (SDM) parts 2015TN and 2015ML enable communication between the TN 1605 and the ML  
10 1620, along with the transport handler (TRH) 2020. In exemplary embodiment(s), a switch device (SD) may correspond to a logical device that terminates a 31 channel logical E1 line. A context handler 2025 controls the connections and connection topology of the domain.

15 In exemplary embodiment(s), an H.248 protocol may be employed for communication over the ATM network. A mapping part portion 2030 stores the topology of one or more MGs 1625 as well as a protocol mapping of the SDM

part(s) (e.g., of the circuit-switched address space) to  
the H.248 (e.g., of the packet-switched address space).  
The exemplary mapping as illustrated at 2050 includes  
indications of an add port instruction 2055 and an add  
5 port response instruction 2060 exchanged between the TN  
1605 and the ML 1620. These instructions, which may  
originate at the MML terminal 2005, configure the mapping  
providing by the H.248 table 2065 and the SD table 2075.  
The H.248 table 2065 and the SD table 2075 together  
10 provide a mapping between H.248 addresses (e.g.,  
termination addresses: "MG/Subrack/Slot/Port" (H.248  
addresses)) and SD addresses (e.g., and "SD1" address).

It should be noted that the H.248 addresses may have  
an unrestricted and/or unstructured format that differs  
15 from and may be more flexible than the  
"MG/Subrack/Slot/Port" as illustrated in FIG. 20B. In  
fact, an operator may be empowered to select such names.  
The MG 1625 includes an H.248 object table 2080, which may

be configured at least in part by the ATM management system 2010, for establishing communication paths through the MG 1625. The tri-level approach described hereinabove in various embodiments enables pre-existing narrowband  
5 technology to be used with broadband technology. Moreover, the tri-level approach multiplies the ability to reuse a pre-existing narrowband switch by enabling a single narrowband switch to provide switching intelligence to multiple broadband switches.

10 Referring now to FIG. 21, an exemplary tri-level nodal environment with exemplary functionality in accordance with the present invention is illustrated generally at 2100. The exemplary tri-level nodal environment 2100 may include a telephony server (TS) 2105  
15 (e.g., which may correspond to, for example, the call server/telephony server 1705 of the embodiment(s) of FIGS. 17A and 17B et seq.). The TS 2105 may include a legacy switch (LS) 2110 (e.g., which may correspond to, for

example, the TN 1605 of the embodiment(s) of FIG. 16 et seq.) and mediation logic (ML) 2115 (e.g., which may correspond to, for example, the ML 1620 of the embodiment(s) of FIG. 16 et seq.). The TS 2105 may also  
5 include a media gateway (MG) 2120 (e.g., which may correspond to, for example, the MG 1615 of the embodiment(s) of FIG. 16 et seq.). It should be noted that the ML 2115 and the LS 2110 may be jointly referred to as a media gateway controller (MGC).

10 The MG 2120 of the TS 2105 may be connected to a broadband network (BN) 2125 (e.g., which may correspond to, for example, the ATM network 215 of the embodiment(s) of FIG. 4 et seq.). The BN 2125 provides a medium for the MG 2120 of the TS 2105 to be in communication with the  
15 other illustrated MGs 2120 (e.g., which may correspond to, for example, the MGs 1625 of the embodiment(s) of FIG. 16 et seq.). It should be understood that the architecture illustrated in the exemplary tri-level nodal environment

2100 may be modified, rearranged, etc., especially in accordance with the other illustrated and described embodiments and teachings from FIGS. 15-15C, as well as those of FIGS. 16-20B. For example, a TS 2105 may omit a  
5 co-located MG 2120 without departing from the spirit and scope of the present invention.

Exemplary functionality is also illustrated in the exemplary tri-level nodal environment 2100. For example, the LS 2110 may include routing analysis in address space-  
10 A functionality 2130 (e.g., which may correspond to, for example, B-number analysis, etc. as described hereinabove with reference to the embodiment(s) of FIGS. 3-3I et seq.). The LS 2110 may also include narrowband telephony services functionality 2135 (e.g., which may correspond  
15 to, for example, those services provided internally by the LS 2110 as well as those services provided externally via the LS 2110 as described hereinabove with reference to the embodiment(s) of FIGS. 3-3I et seq., including those

described by the text related to FIG. 12). Another exemplary functionality illustrated in the exemplary tri-level nodal environment 2100 is mapping from address space-A to address space-B functionality 2140 of the ML 2115. The mapping from address space-A to address space-B functionality 2140 (e.g., which may correspond to, for example, the mapper 1585 of the embodiment(s) of FIGS. 15-15C et seq., the mapping part portion 2030 of the embodiment(s) of FIG. 20A, the tables 2065 and 2075 of the embodiment(s) of FIG. 20B, etc.) enables a conversion from, for example, a narrowband network (e.g., for which the LS 2110 may have originally been designed) to a broadband network (e.g., such as the BN 2125 in which the MGs 2120 may be operating).

FIG. 22 illustrates an exemplary load distribution embodiment in a tri-level nodal environment illustrated generally at 2200. The tri-level nodal environment 2200 shown in FIG. 22 is a portion of the tri-level nodal

environment 2100 illustrated in FIG. 21. For example, in  
FIG. 22, only the media gateway controller (MGC) 2210 that  
includes the legacy switch (LS) 2110 and mediation logic  
(ML) 2115 is shown. However, it should be understood that  
5 the tri-level nodal environment 2200 of FIG. 22 can be  
extended to include the telephony server (TS) shown in  
FIG. 21.

Each call within the tri-level nodal environment 2200  
is handled by a call processor 2230 within the ML 2115.  
10 The call processor 2230 implements a Gateway Control  
Protocol (GCP) 2240 that encodes and decodes messages  
according to the H.248 standard. The call processor 2230  
further includes a transport handling function (TRF) 2245  
for establishing and monitoring transport links 2260  
15 between the call processor 2230 and the MGs 2120 and for  
sending and receiving of messages.

At least one call processor 2230 serves as an  
Operation and Maintenance (OM) call processor (not shown)

that is responsible for maintaining the status of all of the transport links 2260 and call processors 2230. Each call processor 2230 is either a primary call processor or a stand-by call processor. A set of one primary call processor and one stand-by call processor is referred to as a node pair 2250. The primary call processor is referred to as a call handler (CH) 2220.

Within the ATM network, each transport link 2260 is a physical Signaling ATM Adaption Layer (SAAL) transport link that carries H.248 messages between the ML 2115 and the MGs 2120. The H.248 signaling protocol limits the number of active physical SAAL transport links 2260 to one per MG 2120. Therefore, each MG 2120 has only one physical SAAL transport link 2260 to the ML 2115. Each SAAL transport link 2260 terminates at one CH 2220 within the ML 2115. Therefore, there is only one CH 2220 within the ML 2115 that has a SAAL transport link 2260 to a particular MG 2120.



Referring now to FIG. 23, instead of assigning all calls routed through a selected MG (2120 shown in FIG. 22) to the CH 2220 with the SAAL transport link (2260 shown in FIG. 22) to that selected MG, the LS 2110 can include a

5 load distribution function (LDF) 2310 that assigns CH's 2220 on a load basis. The LDF 2310 distributes the load amongst the CH's 2220 to prevent overloading or under-use of any of the CH's 2220. A CH 2220 is assigned for a call by the LDF 2310 sending an Establish Path message 2320

10 from the LS 2110 to the particular CH 2220 in the ML 2115 using the Point Association (PA) of the CH 2220. Upon receipt and assignment by the particular CH 2220, the ML 2115 sends an Establish Path Response message 2325 to the LDF 2310 in the LS 2110. Thereafter, the PA is used to

15 route message to the assigned CH 2220.

In one embodiment, the LDF 2310 assigns the CH's 2220 on a round-robin basis, in which the CH's 2220 are assigned in order from the first CH 2220 to the last CH

2220 and back to the first CH 2220. However, it should be understood that any type of load sharing method can be used to assign the CH's 2220. For example, the LDF 2310 may maintain load information on each of the CH's 2220, and select a particular CH 2220 based on the load information.

FIG. 24 illustrates an exemplary message encoding and transmission embodiment in the tri-level nodal environment. After a CH 2220a has been assigned for the call, all messages 2410 transmitted from the LS 2110 to the selected MG 2120 for the call are routed to the assigned CH 2220a within the ML 2115. The assigned CH 2220a uses the GCP to encode the message 2410 (e.g., convert the message from an internal (Erlang) format into a format specified by the H.248 standards for transmission across the BN 2125 to the selected MG 2120. As mentioned above in connection with FIG. 22, within the ATM network, only one CH 2220 has a physical SAAL transport link 2260

to the selected MG 2120. Therefore, if the assigned CH 2220a does not have the SAAL transport link 2260 to the selected MG 2120, the assigned CH 2220a passes the encoded message 2415 to the linked CH 2220b for transmission to  
5 the selected MG 2120 over the SAAL transport link 2260.

FIG. 25 illustrates an exemplary message decoding and transmission embodiment in the tri-level nodal environment. All messages 2510 sent from the selected MG 2120 to the LS 2110 are received at the linked CH 2220b  
10 within the ML 2115 that has the physical SAAL link 2260 to the selected MG 2120. The linked CH 2220b decodes the message 2510 for transmission to the LS 2110. However, if the linked CH 2220b is not the assigned CH 2220a for the call, the linked CH 2220b passes the decoded message 2515  
15 to the assigned CH 2220a for transmission to the LS 2110. Therefore, although load sharing for messages 2410 (shown in FIG. 24) sent from the LS 2110 to the ML 2115 is achieved by assigning CH's 2220 on round robin and CH load

basis, load sharing for messages 2510 sent from the MG 2120 to the LS 2110 is not possible due to the H.248 signaling protocol requirement of a single active SAAL transport link 2260 to the MG 2120.

5           FIGs. 26A and 26B illustrate an exemplary method in flowchart form for transmitting messages between nodes within a tri-level nodal environment in accordance with the present invention. When the LS has assigned a certain CH for a particular new call (step 2600), the LS sends an  
10   Establish Path message for the call to the assigned CH in the ML using the PA of the assigned CH (step 2605). In response, the CH sends an Establish Path Response message back to the LS (step 2610). Thereafter, when the LS sends a message to the selected MG for the call (step 2615), the  
15   message includes the PA of the assigned CH, so that the ML can forward the message to the assigned CH (step 2620). The assigned CH encodes the message (step 2625) into the

format suitable for transmission across the BN to the selected MG.

If the assigned CH does not have the SAAL transport link to the selected MG (step 2630), the assigned CH  
5 passes the encoded message to the linked CH that has the SAAL transport link to the selected MG (step 2635) for transmission of the encoded message to the selected MG (step 2640). However, if the assigned CH does have the SAAL transport link to the selected MG (step 2630), the  
10 assigned CH transmits the encoded message directly to the selected MG via the SAAL transport (step 2640).

Referring now to FIG. 26B, when the selected MG sends a message to the LS for the call (step 2650), the message is received at the linked CH having the SAAL transport  
15 link to the selected MG (step 2655). The linked CH decodes the message (step 2660) into a format suitable for transmission to the LS. If the linked CH is the assigned CH (step 2665), the linked CH transmits the decoded

message directly to the LS (step 2675). However, if the linked CH is not the assigned CH (step 2665), the linked CH passes the decoded message to the assigned CH (step 2670) for transmission to the LS (step 2675).

5           Although embodiment(s) of the methods, systems, and arrangements of the present invention have been illustrated in the accompanying Drawings and described in the foregoing Detailed Description, it will be understood that the present invention is not limited to the  
10           embodiment(s) disclosed, but is capable of numerous rearrangements, modifications, and substitutions without departing from the spirit and scope of the present invention as set forth and defined by the following claims.